

# Temperature Control Baths

Temperature Bath Systems combine state-of-the-art controller displays with high performance circulating baths to give accurate viscosity test results

All controllers are swivel-mounted so that user can adjust position for optimum viewing angle



## AP Series Controllers

- Color touch-screen interface
- Standalone programmable or PC control with RheocalcT software
- Variable-speed pump
- Max. temperature up to 200°C
- Multiple languages (English, French, German, Spanish, Chinese available)
- Built-in help menu



## SD Series Controllers

- Best value
- Programmable with PC control using RheocalcT software
- Quick scroll to set temperature in standalone mode
- 2-speed pump
- Maximum temperature up to 170°C



## MX Series Controllers

- Economical
- Large character display
- Single-speed pump
- Maximum temperature up to 135°C

## Step 1: Choosing the controller

CHOOSE THE ONE THAT BEST SUITS YOUR APPLICATION

- Choose the controller by considering factors such as the need for PC control using RheocalcT with DV2T or DV3T, ease of use, pump speed, and foreign language choices (AP series controller only).

## Temperature Baths Features

MODEL	Temperature Range Low	Temperature Range High	Controller	Cooling	Temperature Stability†	Digital Type/Resolution (Set / Read)	Reservoir Capacity	Pump Speed	Maximum Flow Rate	Internal Work Area (inches)	Overall Dimensions (inches)	Weight (Gross)
TC-650AP	-20°C	+200°C	AP	Refrigerated	0.01°C	0.01 / 0.001	7.0 liters	Variable	16 LPM	6.18 x 5.59 x 5.0	21.3 x 8.7 x 24.3	90 lbs
TC-650SD	-20°C	+170°C	SD	Refrigerated	0.04°C	0.1 / 0.1	7.0 liters	2-speed	11 LPM	6.18 x 5.59 x 5.0	21.3 x 8.7 x 24.3	90 lbs
TC-650MX	-20°C	+135°C	MX	Refrigerated	0.07°C	0.1 / 0.1	7.0 liters	1-speed	12 LPM	6.18 x 5.59 x 5.0	21.3 x 8.7 x 25.4	84 lbs
TC-550AP	-20°C	+200°C	AP	Refrigerated	0.01°C	0.01 / 0.001	7.0 liters	Variable	16 LPM	6.18 x 5.59 x 5.0	23.2 x 16.2 x 16.2	90 lbs
TC-550SD	-20°C	+170°C	SD	Refrigerated	0.04°C	0.1 / 0.1	7.0 liters	2-speed	11 LPM	6.18 x 5.59 x 5.0	23.2 x 16.2 x 16.2	90 lbs
TC-550MX	-20°C	+135°C	MX	Refrigerated	0.07°C	0.1 / 0.1	7.0 liters	1-speed	12 LPM	6.18 x 5.59 x 5.0	23.2 x 16.2 x 17.3	84 lbs
TC-250AP*	ambient +10°C†	+150°C	AP	Tap Water	0.01°C	0.01 / 0.001	10.0 liters	Variable	16 LPM	5.0 x 11.0 x 6.0	13.9 x 13.5 x 14.9	45 lbs
TC-250SD*	ambient +10°C†	+150°C	SD	Tap Water	0.04°C	0.1 / 0.1	10.0 liters	2-speed	11 LPM	5.0 x 11.0 x 6.0	13.9 x 13.5 x 14.9	45 lbs
TC-250MX*	ambient +10°C†	+135°C	MX	Tap Water	0.07°C	0.1 / 0.1	10.0 liters	1-speed	12 LPM	5.0 x 11.0 x 6.0	13.9 x 13.5 x 16.0	39 lbs
TC-150AP*	ambient +10°C†	+150°C	AP	Tap Water	0.01°C	0.01 / 0.001	6.0 liters	Variable	16 LPM	4.5 x 4.0 x 6.0	13.4 x 8.1 x 14.9	26 lbs
TC-150SD*	ambient +10°C†	+150°C	SD	Tap Water	0.04°C	0.1 / 0.1	6.0 liters	2-speed	11 LPM	4.5 x 4.0 x 6.0	13.4 x 8.1 x 14.9	26 lbs
TC-150MX*	ambient +10°C†	+135°C	MX	Tap Water	0.07°C	0.1 / 0.1	6.0 liters	1-speed	12 LPM	4.5 x 4.0 x 6.0	13.4 x 8.1 x 16.0	20 lbs
TC-351	-20°C	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	14.0 x 14.0 x 14.0	72 lbs

\* For use at lower temperatures, use the built-in tap water cooling, or use model TC-351 Cooler for control to -20°C.

† Low temperature limit 10°C above ambient unless external cooling is used.

‡ Temperature stability may vary depending on bath volume, surface area, insulation and type of fluid

N/A - Not Applicable

FOR OPERATING TEMPERATURES HIGHER THAN 80°C, PLEASE CONTACT BROOKFIELD FOR BATH FLUID RECOMMENDATIONS.

## Step 2: Choosing the bath

CHOOSE THE CIRCULATING BATH THAT MEETS YOUR NEEDS

Determine the type of circulating bath needed by considering temperature range, cooling requirements, reservoir capacity, flow speeds and built-in drains (Models TC-550 and TC-650).

# TC-550

PC control capable  
with RheocalcT software

## Circulating Water Bath Refrigerated

- Most popular choice with widest temperature control capability
- 7-liter reservoir capacity
- Configured to measure viscosity directly in the bath or circulate to external water-jacketed devices\*\*
- Accommodates one 600 mL beaker
- Provides stand-alone operation with no tap water required and easy control of set-point
- Available with MX, SD or AP Controllers
- Automated sample temperature control available with SD and AP Controllers



# TC-650

PC control capable  
with RheocalcT software

## Circulating Water Bath Refrigerated

- Compact — small “footprint” on your lab bench or can be placed underneath lab bench
- 7-liter reservoir capacity
- Specifically designed for circulating to external water-jacketed devices\*\*
- Accommodates one 600 mL beaker
- Provides stand-alone operation with no tap water required and easy control of set-point
- Available with MX, SD or AP Controllers
- Automated sample temperature control available with SD and AP Controllers



\*Provided tap water temperature is 15°C or lower

\*\*All baths can be used with Brookfield water jacketed devices; Wells-Brookfield Cone/Plate Viscometer, R/S-CC and R/S-CPS Rheometers and Small Sample Adapter, Ultra-Low Adapter and DIN Adapter accessories

# TC-150

## Circulating Water Bath Non-Refrigerated

Compact – smallest “footprint” available  
6-liter reservoir capacity

Removable deck lid accommodates  
one 600 mL beaker to measure viscosity  
directly in the bath

Tap water cooling coil for  
temperature control at 25°C\*

Built-in circulator pump for use  
with external water-jacketed devices\*\*

Available with MX, SD or AP Controller

MX Controller  
shown



## Water Bath Accessories

Algicide 8 oz.

TC-Fluid 1A

Keeps circulator baths clean,  
odor free and resists black algae

50/50 Premix  
Ethylene Glycol 1 gal.

TC-Fluid 2 -20°C to +100°C

Ethylene glycol 1:1 solution, ready to use

High Temperature Fluid 1 gal.

TC-Fluid 3 +50°C to +150°C

TC-Fluid 4 +100°C to +200°C

PVS-152 +25°C to +200°C

These heat transfer fluids provide superior  
thermal stability

Low Temperature Fluid 1 gal.

TC-Fluid 5 -50°C to +58°C

Excellent low temperature performance  
Little or no evaporation

Bath Cleaner 8 oz.

TC-Fluid 6A

Removes rust and mineral deposits  
Concentrated liquid

18" Lab Stand Rod

VS-CRA-18S

Designed for increasing viscometer height  
when measuring in a TC-150, TC-250 or TC-550  
Bath

# TC-250

PC control capable  
with RheocalT software

## Circulating Water Bath Non-Refrigerated

Largest work area available  
for conditioning multiple samples  
directly in the bath

10-liter reservoir capacity

Accommodates 600 mL and  
1000 mL beakers (cover is  
removable for large sample  
container requirements)

Built-in tap water cooling coil  
for temperature control at 25°C\*

Built-in circulator pump for use  
with external water-jacket devices\*\*

Available with MX, SD or AP Controller

SD Controller  
shown



# TC-351

Cooler (not shown) for use with TC-150 & TC-250 Circulating Baths

Eliminates tap water requirements on non-refrigerated baths  
Increases lower range of most baths to -20°C

## Step 3: Comparing bath features

Once you've familiarized yourself with the Brookfield Circulating Water Bath Series  
you can easily compare models to find the bath that best suits your requirements.



## Accessories

Additional benches for elevating the  
position of beakers, metal lids for anchoring  
beakers, hoses, and deck lid covers are  
available. Contact us for details.

