




## DT-129/129B

Moisture Meters DT-129 is a conductivity moisture instrument designed for use in wood, used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). They display the moisture level. The instruments have an average adjustment for European wood based on a wood temperature of 20°C. DT-129B is with various professional remote probe. Large LCD display Automatically Temperature Corrected (ATC) Readings when used with the temperature probe Readings with Moisture Probe or Hammer Electrode Readings with Integral electrode Pins.



<b>Features:</b>
1.Large LCD display
2.Automatically Temperature Corrected(ATC) Readings when used with the temperature probe
3.Readings with Moisture Probe or Hammer Electrode
4.Readings with Integral electrode Pins

<b>Specifications:</b>	
Measuring principle	Electrical resistance
Electrode length	8mm
Electrodes	Integrated, replaceable
Measuring range	Wood:6-99.9%
Display Accuracy	Wood: ±1%
Battery	2×AAA
Temperature measuring	0-60°C
Ambient temperature	0-40°C
Ambient moisture	0-85%




**Moisture Meters**

DT-129 is a conductivity moisture instrument designed for use in wood, used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). They display the moisture level. The instruments have an average adjustment for European wood based on a wood temperature of 20°C.

DT-129B is with various professional remote probe.

- Large LCD display
- Automatically Temperature Corrected (ATC) Readings when used with the temperature probe
- Readings with Moisture Probe or Hammer Electrode
- Readings with Integral electrode Pins



Size(HxWxD): 180mm x 50mm x 31mm  
 Weight: 175g

Accessories :  
 Gift Box with Carrying Case