




DT-179


Carbon Monoxide Datalogger Alarm setup and indication; Recording and low battery indication; Manual and automatic start mode; USB port for data traffic and power supply; Status indication via Red/Yellow LED and Green LED; Analysis software windows 98/2000/XP/Vista/7. Memory 32000 readings Measuring rate 2sec. to 24h Measurement Range 0 to 1000PPM Measurement Resolution 1PPM Accuracy $\pm 5\%$ or $\pm 10\text{PPM}$ Warm up period Less than 2 seconds Sensor type Stabilized electrochemical Gas-specific (CO) Typical sensor life 3 years.



Features	
Alarm setup and indication	
Recording and low battery indication	
Manual and automatic start mode	
USB port for data traffic and power supply	
Status indication via Red/Yellow LED and Green LED	
Analysis software windows 98/2000/XP/Vista/7	


Specifications	
Memory	32000 readings
Measuring rate	2sec. to 24h
Measurement Range	0 to 1000PPM
Measurement Resolution	1PPM
Accuracy	±5% or ±10PPM
Warm up period	Less than 2 seconds
Sensor type	Stabilized electrochemical Gas-specific (CO)
Typical sensor life	3 years





Carbon Monoxide Datalogger
Alarm setup and indication; Recording and low battery indication; Manual and automatic start mode; USB port for data traffic and power supply; Status indication via Red/Yellow LED and Green LED; Analysis software windows 98/2000/XP/Vista/7.

Memory: 32000 readings
Measuring rate: 2sec. to 24h
Measurement Range: 0 to 1000PPM
Measurement Resolution: 1PPM
Accuracy: ±5% or ±10PPM
Warm up period: Less than 2 seconds
Sensor type: Stabilized electrochemical Gas-specific (CO)
Typical sensor life: 3 years



Size(HxWxD): 145mm x 35mm x 30mm

Weight: 49g

Accessories: 3.6V Lithium battery, software and clamshell.