




DT-317/317B/318/318B


Flexible Thermo-Anemometers 16" inch Gooseneck detector is easy to measure the hard-to-reach areas. High Sensitive and Accurate Easy-to-use design Double LCD digital display Low power consumption Data Hold and MAX Hold function Low battery indication.




Features
16" inch Gooseneck detector is easy to measure the hard-to-reach areas.
High Sensitive and Accurate
Easy-to-use design
Double LCD digital display
Low power consumption
Data Hold and MAX Hold function
Low battery indication


Specifications			
Air Velocity	Range	Resolution	Accuracy
m/s(meter per second)	1.0~30.00	0.01	±3% ±0.20m/s
ft/min(feet per minute)	196~5900	1	±3% ±40ft/min
km/h(kilometers per hour)	3.6~108.0	0.1	±3% ±0.8km/h
MPH(miles per hour)	2.2~67.0	0.1	±3% ±0.4MPH
Knots(nautical miles per hour)	1.9~58.0	0.1	±3% ±0.4knots
Air Temperature	-10~60°C(14~140°F)	0.1°C/°F	± 2.0°C(4.0°F)
Air Flow	Range	Resolution	Area
CFM (317B/318B)	0-999900	0.1	0-999.9 ft2








Temperature



CFM
Air Flow



Backlight

16" inch Gooseneck detector

Flexible Thermo-Anemometers

16" inch Gooseneck detector is easy to measure the hard-to-reach areas.

High Sensitive and Accurate


Easy-to-use design

Double LCD digital display

Low power consumption

Data Hold and MAX Hold function

Low battery indication



Size(HxWxD): 163mm x 45mm x 34mm

Weight: 210g

Accessories : 9V battery and Anemo probe, Gift box with carrying case.