

DT-330H Series

Mini AC, AC/DC Autoranging Clamp Meters



The 330H series are designed to verify the presence of load current, voltage and resistance, etc. The small bodies and jaws fit perfectly in your hand and a large backlit display is easy to read.

Features

	330H	331H	332/332T	333/333T	335	336
Max. Resolution to	AC	AC	AC/DC	AC/DC	AC	AC/DC
Current measurement	1mA	10mA	10mA	10mA	0.1uA	0.1uA
LCD display counts	2000	4000	4000	4000	4000	4000
AC True RMS	*	*	332T	333T		
Display with backlight	*	*	*	*	*	*
Data Hold	*	*	*	*	*	*
Max Hold	*	*				
Zero Function			*	*	*	*
0.9" (23mm) Jaw size	*	*	*	*	*	*

Specifications

Function	Max Range	Basic Accuracy	330H	331H	332	333	335	336
Voltage DC	600V	±(0.5%+1d)	*	*	*	*	*	*
Voltage AC	600V	±(1.5%+2d)	*	*	*	*	*	*
Current DC	400A	±(2.5%+5d)			*	*		
Current AC	400A	±(3.0%+4d)	*	*	*	*	*	*
Resistance	20MΩ	±(3.0%+5d)	*	40MΩ	40MΩ	40MΩ	40MΩ	40MΩ
Temperature	1000°C/1832°F	±(3.0%+3d)		*		*	*	
Capacitance	100uF	±(2.5%+5d)		4mF	*	*	*	*
Frequency	150KHz	±(1.2%+2d)		10kHz	*	*	*	
	10MHz							*
Continuity	Buzzer sounds at 100Ω		50Ω	50Ω	*	*	*	*
Diode	Test current 0.3mA; Open circuit voltage 1.5V		*	*	*	*	*	*

Size(HxWxD): 205mm x 70mm x 37mm **Weight:** 200g

Accessories: Test leads, gift box with carrying case, temperature probe (331H, 333, 335 only) and Two "AAA" 1.5V batteries.



EMC & LVD

EN: 61326

EN: 61010-1

EN: 61010-02-032

EN: 61010-02-033



Model 330H