

350H series clamp meters offer all the features you need to fit the way you work. The small bodies and jaws fit perfectly in your hand and into tight places. Slender housing design is good to measure by one hand. A large backlit display (on most models) is easy to see and a handy display hold keeps measurements on the display. Measuring starting current for motors, lighting, etc.

- Double molded plastic housing
- Auto Power Off



EMC & LVD  
 EN: 61326  
 EN: 61010-1  
 EN: 61010-02-032  
 EN: 61010-02-033



**Model 350H**



**Model 351H**

**Size(HxWxD):** 198mm x 66mm x 36mm

**Weight:** 230g

**Accessories:** Test leads, gift box with carrying case, temperature probe and two "AAA" 1.5V batteries.

**Features**

	350H	351H	352
Current measurement	AC	AC/DC	AC
LCD display counts	4000	4000	2000
AC True RMS	*	*	*
Data Hold	*	*	*
REL(Zero) Function	*	*	*
Auto Power Off	*	*	*
Low battery indication	*	*	*
1.2"(30mm) Jaw opening	*	*	*
NCV Detection	*	*	*

**Specifications**

Function	Max. Range	Max Resolution	Best Accuracy	350H	351H	352
Voltage DC	600V	100 $\mu$ V	$\pm(0.5\%+8d)$	*	*	*
Voltage AC	600V	1mV	$\pm(1.2\%+3d)$	*	*	*
Current DC	400A	10mA	$\pm(2.5\%+5d)$		*	
Current AC	400A	10mA	$\pm(2.5\%+5d)$	*	*	1mA
Resistance	40M $\Omega$		$\pm(2.0\%+3d)$	*	*	20M $\Omega$
Temperature	760°C/1400°F		$\pm(1.5\%+5d)$	*	*	*
Capacitance	4mF		$\pm(3.0\%+5d)$	*	*	
Frequency	10kHz		$\pm(1.2\%+5d)$	*	10kHz	
Continuity check	Buzzer sounds at 50 $\Omega$					
Diode test	Test current 0.5mA					