

DT-355/355H/355W/356/356H/356W/357

Professional AC, AC/DC True RMS Autoranging Clamp Meters



The 355 series clamp meters offer all needed features for measurement. They are small bodies and jaws design for perfect handhold and tight place testing. A large backlit display (on most models) is easy to see and a handy display hold keeps measurements on the display.

- Double molded plastic housing
- True RMS measurement for ACV & ACA
- Auto Power Off



| Features | 355 | 355H | 356 | 356H | 357 | 355W | 356W |
|---------------------------|------|------|-------|-------|-------|---------|--------|
| Current measurement | AC | AC | AC/DC | AC/DC | AC/DC | AC | AC/DC |
| LCD display counts | 6000 | 6000 | 6000 | 6000 | 40000 | 6000 | 6000 |
| AC True RMS | * | * | * | * | * | * | * |
| Display with backlight | * | * | * | * | * | * | * |
| Data Hold | * | * | * | * | * | * | * |
| Max /Min | * | * | * | * | * | * | * |
| REL (Zero) Function | * | * | * | * | * | * | * |
| Auto Power Off | * | * | * | * | * | * | * |
| Low battery indication | * | * | * | * | * | * | * |
| Analog Bargraph / 61 seg. | * | * | * | * | * | * | * |
| 1.57" (40mm) Jaw opening | * | * | * | * | * | * | * |
| NCV Detection | * | * | * | * | * | * | * |
| USB interface | | | | | | * | * |
| Wireless transmitter | | | | | | 433MHz | 915MHz |
| Receive sensitivity | | | | | | -109dBm | |
| Communication distance | | | | | | ≤ 100m | |

| Specifications | Function | Max Range | Basic Accuracy | 355/355W | 355H | 356/356W | 356H | 357 |
|------------------|----------------------|------------|----------------|----------|------|----------|------|-----|
| Voltage DC | 600V | ±(0.5%+1d) | * | * | * | * | * | * |
| Voltage AC | 600V | ±(1.5%+2d) | * | * | * | * | * | * |
| Current DC | 1000A | ±(2.0%+5d) | | | * | * | * | * |
| Current AC | 1000A | ±(2.8%+8d) | * | * | * | * | * | * |
| Resistance | 60MΩ | ±(3.0%+5d) | * | * | * | * | * | * |
| Temperature | 760°C/ 1400°F | ±(3.0%+3d) | * | * | * | * | * | * |
| Capacitance | 4000uF | ±(2.5%+5d) | * | 4mF | * | 4mF | * | * |
| Frequency | 10kHz | ±(1.2%+2d) | * | * | * | * | * | * |
| Inrush Current | 600A | ±(1.5%+2d) | | | | | | |
| Continuity check | Buzzer sounds at 50Ω | | | | | | | |
| Diode test | Test current 0.3mA | | | | | | | |



Model 356



Model 356H

Size(HxWxD): 230mm x 76mm x 40mm

Weight: 315g

Accessories: Test leads, gift box with carrying case, temperature probe and 9V battery.
USB cable and Software(355W/356W)

