

# DT-371/371B/371BL/372/372H/373/373H/375/375BT

## Compact AC, AC/DC Autoranging Clamp Meters



The 371 series clamp meters offer all needed features for measurement. They are with small bodies and jaws designed for perfectly handhold and tight place testing. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display.

- Double molded plastic housing
- Auto Power Off



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-032  
EN: 61010-02-033



True RMS (372H/373H/375/375BT)

1.2" (30mm) Jaw opening



Model 371

Model 373

### Features

	371	371B	371BL	372	372H	373	373H	375	375BT
Current measurement	AC	AC	AC	AC	AC	AC/DC	AC/DC	AC/DC	AC/DC
Max. Resolution	1mA	1mA	1mA	1mA	10mA	10mA	10mA	10mA	10mA
LCD display counts	2000	2000	2000	4000	4000	4000	4000	4000	6000
AC True RMS	*				*		*	*	*
Display with backlight	*	*	*	*	*	*	*	*	*
Data Hold	*	*	*	*	*	*	*	*	*
Max Hold	*				*		*	*	*
Zero Function						*	*	*	*
Auto Power Off	*	*	*	*	*	*	*	*	*
Low battery indication	*	*	*	*	*	*	*	*	*
Bluetooth									*
1.2" (30mm) Jaw opening	*	*	*	*	*	*	*	*	*

### Specifications

Function	Max Range	Basic Accuracy	371	371B	371BL	372	372H	373	373H	375	375BT
Voltage DC	600V	±(0.5%+1d)	*	*	*	*	*	*	*	*	*
Voltage AC	600V	±(1.5%+2d)	*	*	*	*	*	*	*	*	*
Current DC	400A	±(2.0%+5d)						*	*	*	*
Current AC	400A	±(2.5%+4d)	*	*	*	*	*	*	*	*	*
Flexible A	3000A	±(3.0%+5d)									*
Resistance	40MΩ	±(3.0%+5d)	20MΩ	20MΩ	20MΩ	*	*	*	*	*	60MΩ
Temperature	1000°C/1832°F	±(3.0%+3d)		*			*		*	*	*
Capacitance	100µF	±(2.5%+5d)					4000µF	*	4000µF	4000µF	6000µF
Frequency	10MHz	±(1.2%+2d)				*	10kHz	*	10kHz	*	*
Continuity check	Buzzer sounds at 50Ω		*	*	*	30Ω	50Ω	30Ω	50Ω	*	*
Diode test	Test current 0.3mA		*	*	*	*	*	*	*	*	*

Size(HxWxD): 197mm x 70mm x 40mm

Weight: 183g

Accessories: Test leads, gift box with carrying case, temperature probe(371B,372H/373H/ 375, 375BT only), 1.5Vx2 "AAA" batteries.