



DT-390/391

390/391 clamp meter offers all needed features for measurement. It has small bodies and jaws design for perfectly handhold and tight place testing. A large backlit display is easy to see and a handy Display Hold keeps measurements on the display. Measuring starting current for motors, lighting, etc.

Accessories



Features		
	390	391
200A AC Current measurement	*	*
Digital display counts	6000	6000
Display type(Negativity display)	*	*
Compact size	*	*
Data Hold & MAX/MIN Function	*	*
Peak Value & Inrush Current		*
Backlight for button, knob Switch & Flashlight	*	*
Low battery indication	*	*
17mm Jaw opening	*	*
Auto sense Voltage	*	*
NCV	*	*
Low Z & True RMS	*	*
Non contact voltage test		*

Specifications				
Function	Max Range	Basic Accuracy	390	391
Voltage DC	1000V	$\pm(0.8\%+3d)$	*	*
Voltage AC	1000V	$\pm(1.0\%+3d)$	*	*
Current AC	200A	$\pm(3.5\%+5d)$	*	*
Resistance	60MΩ	$\pm(3.0\%+5d)$	*	*
Capacitance	6000mF	$\pm(2.5\%+5d)$	*	*
Non contact voltage test	600V	$\pm(2.5\%+5d)$		*
LoZ (<600V)			~3KΩ	
Continuity check	Buzzer sounds at 50Ω			
Diode test Test	current 0.35mA 3V			