





DT- 805/805L


Series Sound Level Meters Provides 1.4dB accuracy (805); Provides 2.0dB accuracy (805L) Meets IEC61672-1 Type 2 (805) Newly Design Shape High Performance Max Hold and Data Hold Function.




| Features | |
|---|--|
| Provides 1.4dB accuracy (805); Provides 2.0dB accuracy (805L) | |
| Meets IEC61672-1 Type 2 (805) | |
| Newly Design Shape | |
| High Performance | |
| Max Hold and Data Hold Function | |

| Specifications | |
|---------------------|--|
| Level Range | Low = 30 ~ 100dB |
| | High = 60 ~ 130dB |
| Accuracy | ±1.4dB (ref 94dB @ 1kHz) |
| Frequency Range | 31.5Hz to 8kHz |
| Frequency Weighting | A, C |
| Time Weighting | Fast, Slow |
| Battery Type | 9V Battery NEDA 1604, IEC 6F22, JIS 006P |
| Operation Temp | 0°C~40°C(<80%R.H.) |
| Storage Temp | -10°C~60°C(<70%R.H.) |





Series Sound Level Meters

Provides 1.4dB accuracy (805); Provides 2.0dB accuracy (805L)
 Meets IEC61672-1 Type 2 (805)
 Newly Design Shape
 High Performance
 Max Hold and Data Hold Function

