





DT-855/855S


Sound Level Meter DT-855/855S Sound Level Meters are designed for noise project, quality control, illness prevention & cure and all kinds of environmental sounds measurements. It is applied to the sounds measurement at factory, school, office, traffic access and household etc.




Features	DT-855	DT-855S
This unit confirms to the IEC61672-1 class 2 for Sound Level Meters	*	*
MAX & MIN measurements	*	*
Overrange & Underrange display	*	*
A & C Weighting	*	*
FAST & SLOW response	*	*
Analog AC/DC outputs for connection to frequency analyzer or X-Y shaft recorder	*	*
Datalogger function	*	*
Adjustable Alarm-Levels	*	*
Memory for 32700 readings	*	
2GB Micro SD memory card		*
Bluetooth interface to smartphone/PC		*

Specifications	
Standard	IEC61672-1 Type 2, ANSI S1.4 Type2
Accuracy	± 1.4dB
Frequency range	31.5Hz ~ 8kHz
Dynamic range	50dB
Level ranges	Lo:30dB~80dB Med:50dB~100dB Hi:80dB~130dB Auto:30dB~130dB
Time weighting	FAST (125mS), SLOW (1s)
Microphone	1/2 inch electret condenser microphone
Resolution	0.1dB
Display Update	2 times/sec
Analog output	AC/DC outputs, AC=1Vrms, DC=10mV/dB







30~130 dB



DATA LOGGER




Backlight

• Level range: 30~130dB

• 1.4dB Accuracy

Sound Level Meter
DT-855/855S Sound Level Meters are designed for noise project, quality control, illness prevention & cure and all kinds of environmental sounds measurements. It is applied to the sounds measurement at factory, school, office, traffic access and household etc.



Size(HxWxD): 248mm x 65mm x 45mm

Weight: 248g

Accessories : 9V battery, gift box and carrying case.