




## DT-857/857A

857/857A Hot Wire Anemometer makes a step forward for you into the field of precision measurement. Telescoping probe is ideal for measuring in HVAC ducts and other small vents; extends up to 20m/s.



Features		
	857	857A
Single-point and continuous data log options	*	*
Velocity alarm	*	*
LED backlight	*	*
Auto power off	*	*
Low-battery indication	*	*
Data hold	*	*
Probe sensor cover	*	*
Replaceable probe sensor		*

Specifications			
Air/Velocity	Range	Resolution	Accuracy
m/s(meter per second)	0.1~20m/s	0.01m/s	±5%+0.03m/s
ft/min(feet per minute)	20~3937ft/min	1 ft/min	±5%+6ft/min
km/h(kilometers per hour)	0.3~72km/h	0.1km/h	±5%+0.1km/h
MPH(miles per hour)	0.2~44.7MPH	0.1MPH	±5%+0.1 MPH
Air Temperature	- 20~60°C (- 4~140°F)	0.1°C/0.1°F	0.5°C(0~45°C), 1.0°C(rest of range) 1.0°F(32~113°F), 2.0°F(rest of range)




CE

**Professional Multifunction Environment Meters**


The digital Multifunction Environment Meter has been designed to combine the functions of Sound Level Meter, Light Meter, Humidity Meter, Type K Thermometer, Anemometer. It is an ideal Multifunction Environment Meter with scores of practical applications for professional and home use.

• dB, %RH, Anemo & Temperature meter


• 5 in 1



Air Flow



Temperature




0-100% RH



35-100 dB



LUX  
FC  
Light (LUX/FC)



**Accessories :** 3.7 Li battery, USB cable, software, Carrying case and Gift box.

