




DT-8850

Sound Level Meter DT-8850 Sound Level Meter can be used to measure noise in factories, schools, offices, airports and home etc, checking acoustics of studios, auditoriums and Hi-Lo installations. 8850 meets IEC 61672-1 Type 2 standards. The 30 to 130 dB range makes this meter ideal for all general purpose sound level measurements.



Features
Provides 1.4dB accuracy
Meets IEC61672-1 type 2 standards
Newly Design Shape
High Performance
Max Hold and Data Hold Functions
Analog AC/DC outputs for connection to an analyzer or recorder
Built-in calibration check

Specifications	
Range	Lo (Low)-Weighting: 35dB~100dB Hi (High)-Weighting: 65dB~130dB
Frequency Weighting: A /C	Lo (Low)-Weighting: 35dB~100dB Hi (High)-Weighting: 65dB~130dB
Resolution	0.1dB
Accuracy	1.4dB at 94dB sound level, 1kHz sine wave
Measurement rate	1.5 times per second, normal
Storage temperature	-10°C~60°C (<80%R.H.)
Over range	"OL" mark indication





CE

• 1.4dB Accuracy

Sound Level Meter

DT-8850 Sound Level Meter can be used to measure noise in factories, schools, offices, airports and home etc, checking acoustics of studios, auditoriums and Hi-Lo installations. 8850 meets IEC 61672-1 Type 2 standards. The 30 to 130 dB range makes this meter ideal for all general purpose sound level measurements.





DC-AC OUTPUT

Size(HxWxD): 251mm x 63.8mm x 40mm
Weight: 250g

Accessories : 9V battery, Carrying case and Gift box.