



DT-983/986/986S

320x240 High Performance Thermal Imager with high resolution TFT screen (986S). Capture additional measurements fastly and conveniently with wireless modules. Image fusion function displays thermal image superimposed over a digital image and easy-to-access thumbnail image gallery helps you to quickly review and find your thermal images. Powerful Auto Fusion mode (AUF). Equipped with standard video, USB outputs as well as a removable SD card. Realtime analyse and picture analyse function. Find problems faster and easier and accurately identify potential issues by combining digital and IR images.



FEATURE

- 320x240 High Performance Thermal Imager with high resolution TFT screen (986S)
- Smart design with big screen occupation ratio
- Capture additional measurements fastly and conveniently with wireless modules
- Find problems faster and easier and accurately identify potential issues by combining digital and IR images
- Image fusion function displays thermal image super-imposed over a digital image and easy-to-access thumbnail image gallery helps you to quickly review and find your thermal images.
- Powerful Auto Fusion mode(AUF)
- Equipped with standard video, USB outputs as well as a removable SD card.
- Realtime analyse and picture analyse function

Accessories:

Hard transport case, 7.5mm lens, Tripod base, AC charger/Power supply, Battery, software CD-ROM, Handstrap, micro SD card, USB cable & RCA cable, Gift box.

Specifications				
		983	986	986s
Imaging and optical data				
IR resolution	Focal plane array (FPA), uncooled microbolometer	80x80	220x160	320x240
Field of View	(FOV)	21°x21°	36°x27°	36°x27°
Spatial resolution	(IFOV)	4.53mrad	3mrad	3mrad
Thermal sensitivity/NETD	< 0.05°C @ +30°C/(+86 ° F) < 0.1°C/100mK	*	*	*
Image frequency	9Hz	*	*	*
Focus	Focus free	*	*	*
Image presentation				
Display	3.5" 640x480 touch screen	*	*	*
Image modes	IR image, visual image, picture in picture, AUF	*	*	*
Color palettes	IRON, Rainbow, Grey, Grey Inverted, Brown, Blue-red, hot-cold, Feather	*	*	*
Measurement				
Object temperature range	Low range: -20°C to +330°C (-4°F to +302°F)	*	*	*
Accuracy	±5°C (±3.6°F) or ±3% of reading	*	*	*
Measurement analysis				
Emissivity adjustable	0.01~1.0 Adjustable	*	*	*
Automatic hot /cold detection	Auto hot or cold spotmeter marks	*	*	*
Set-up				
Laser / floodlight	< class2 / white LED floodlight	*	*	*
Language selection	English, Chinese, French, German, Spanish	*	*	*
Storage of videos/images				
Storage media	4Gbytes eMMC	*	*	*
Video storage format	Standard MPEG-4, 640x480@30fps, on memory card > 60 minutes	*	*	*
Image storage format	Standard JPEG, including measurement data, on memory card > 1000 pictures	*	*	*
Storage mode	IR/visual images; simultaneous storage of IR and visual images	*	*	*
Digital camera				
Built-in visible light digital camera	2M Pixels	*	*	*
Data communication interfaces				
USB interfaces	USB-micro, data transform between camera and PC Remote control, live video	*	*	*
Wi-Fi connectivity	Wi-Fi connectivity allows to send images and data to mobile devices remote control, live video	*	*	*
Power system		*	*	*

Battery	Lithium polymer battery, 4 hours operating time	*	*	*
Input voltage	DC 5V	*	*	*
Charging system	In camera (AC adapter)	*	*	*
Power management	Automatic shutdown and sleep mode (user selectable)	*	*	*

•