



DT-99/99B

DT-99/99B Electrochemical Exhaust Ozone Concentration Detector for gas concentration detection in a variety of industrial environments and special environments, with imported electrochemical sensors and microcontrollers technology for fast response, high accuracy, stability and repeatability , Machine performance ranks the world's leading level, the parameters of the user can customize the settings, simple operation. Using 2.0-inch industrial color screen, the perfect display of the technical indicators and gas concentration values, you can view the historical data on the screen, with storage, data export, temperature and humidity detection and other functions.



Features	
imported electrochemical sensors and ultra-low power 32-bit microprocessors	
2.0-inch industrial grade color screen with a resolution of 220x176	
PPM, mg / m ³ two units of concentration can be free to switch	
has a data storage function, can store 5000 sets of data, you can view the historical data on the screen, you can export data	
with temperature and humidity detection function, can detect the site or the gas temperature and humidity within the pipeline	
built-in powerful pumping device, can work in the micro-negative pressure environment	
Automatic shutdown function	
Bluetooth interface (99B)	

Specifications			
Measuring Range	0~100ppm		
Resolution	0.01ppm		
Air Temperature Range	-20 to 70 °C		
Humidity Range	0 to 100%RH		
Detection	Suction, built-in powerful suction device, flow rate: 50-500mL /min adjustable, can work in the micro-negative environment		
Response time	≤60s	Repeatability	≤±1%
Storage mode	real-time storage, can store data of 5000 group, you can view the historical data on the screen		

Accessories :
3.7V Li-on battery, Clamshell.