



GD-3301

Combustible Gas Leak Detector Easy to Use: It fits comfortably in your hand and operates with the simple push of a button. Fast Response: Pump driven design ensures immediate response. Easy to Read: See the results even in poorly lit areas with the back light, two line LCD display. Quick Set Up: Push zero button is much easier than manual adjust instruments. Calibrate in the Field: No need to send your instrument to the factory for service. Eliminates time.



Features

Easy to Use: It fits comfortably in your hand and operates with the simple push of a button.
Fast Response: Pump driven design ensures immediate response.
Easy to Read: See the results even in poorly lit areas with the back light, two line LCD display.
Quick Set Up: Push zero button is much easier than manual adjust instruments.
Calibrate in the Field: No need to send your instrument to the factory for service. Eliminates time.

Specifications

Pump driven field adjustable range	0-1000ppm
Resolution	1ppm
Response Time	3 seconds, 90% of reading in 30 seconds
Accuracy	±3ppm, ±3% of reading
Operating Temperature	0-104°F, 5-95% Relative Humidity, non condensing
Zero Adjustment	Push Button
Battery	3" C Alkaline
Battery Life	20 hours continuous operation



Combustible Gas Leak Detector

Easy to Use: It fits comfortably in your hand and operates with the simple push of a button.

Fast Response: Pump driven design ensures immediate response.

Easy to Read: See the results even in poorly lit areas with the back light, two line LCD display.

Quick Set Up: Push zero button is much easier than manual adjust instruments.

Calibrate in the Field: No need to send your instrument to the factory for service. Eliminates time.

Size (H x W x D): 221mm x 72mm x 46mm

Weight: 365g