




SC-05


Sound Level Calibrator 94dB and 114dB
Sound Calibration at 1kHz; Accurate
and simple to use; Fits 1/2" diameter
microphone. Output Sound Pressure
Levels 114dB and 94dB re 20 uPa
under reference conditions. Output
Frequency 1000Hz, $\pm 4\%$ Reference
Temperature Conditions $>23^{\circ}\text{C}$ (73°F)
Atmospheric pressure >1013 mbar
(760mm of Hg) Relative humidity
 $>65\%$ RH Accuracy of Sound Pressure
Level Under stated reference environment conditions
 $\pm 0.5\text{dB}$.



Features
94dB and 114dB Sound Calibration at 1kHz
Accurate and simple to use
Fits 1/2" diameter microphone

Specifications	
Output Sound Pressure Levels	114dB and 94dB re 20 uPa under reference conditions.
Output Frequency	1000Hz, ±4%
Reference Temperature Conditions	>23°C (73°F)
Atmospheric pressure	>1013 mbar (760mm of Hg)
Relative humidity	>65%RH
Accuracy of Sound Pressure Level	Under stated reference environment conditions ±0.5dB





Sound Level Calibrator
 94dB and 114dB Sound Calibration at 1kHz; Accurate and simple to use; Fits 1/2" diameter microphone.

Output Sound Pressure Levels 114dB and 94dB re 20 uPa under reference conditions.
 Output Frequency 1000Hz, ±4%
 Reference Temperature Conditions >23°C (73°F)
 Atmospheric pressure >1013 mbar (760mm of Hg)
 Relative humidity >65%RH
 Accuracy of Sound Pressure Level Under stated reference environment conditions ±0.5dB

Size(HxWxD): 120mm x 50mm x 42mm
 Weight: 278g

Accessories: 9V battery, Carrying case, 1/2" Microphone Adaptor (optional) and Clamshell.