



PURISPIN 6 MICRO CENTRIFUGE

Personal mini micro centrifuge



● ● ● STANDARD SPECIFICATION



Max. RPM	6,000RPM
Max. RCF	2,000 xg
Max. Capacity	1.5/2.0ml x 8
Noise Level	≤55dB
RPM Accuracy	±100
Available Rotor Quantity	2
Power Supply	AC 100-220V ± 10%, 50-60Hz
Power Consumption	310W
Dimension(W x D x H)	162 x 154 x 116 mm (H:225mm with open lid)
Weight (without rotor)	1kg

●●● MAIN FEATURE

● Compact Design

small footprint available in any work table.

● Simple Operation

- Electronic breaking system embedded.
- When user opens the lid, the device stops automatically.

● Excellent Durability

Robust structure suitable for repeated operation.

●●● AVAILABLE ROTORS



A81.5M




A160.2M

●●● CONTROLLER

RPM
Display screen



Start/
Stop Switches



●●● ORDER INFORMATION

ITEM	DESCRIPTIONS	ORDER CODE
PURISPIN 6 Set	PURISPIN 6, with rotor A81.5M, PCR Rotor A160.2M including 0.2/0.5ml tube adaptors, 100~220V/50~60Hz	P6 - SET