

DAIHAN® 105 & 295 Lit Blood Bank & Pharmaceutical Refrigerator "BR & PR", 2~10°C, Class-I & II Medical Device NEW
 With Microprocessor PID Controller, 60mm(t) Polyurethane Insulation, Vacuum Sealed Glass Door, CFC/HCFC-Free, Forced Air Circulation
 Drawer or Wire Shelf, Superior Temp Uniformity, 혈액보관용 & 시약약품보관용 냉장고

NEW **Class-II Medical Device**
 2~10°C

(1) 3 STS Drawer Shelf (Included)

Built in Temp Chart Recorder

2-Year Warranty

A. 295Lit Blood Bank Refrigerator "BR-300"

2~10°C **Class-I Medical Device**

(2) 2 Teflon-coated Wire Shelf (Included)

(3) Teflon-coated Wire Basket (Included)

2-Year Warranty

B. 105Lit Pharmaceutical Refrigerator "PR-100"

■ **PL(Product Liability)**

■ **with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System**

- * Energy Saving LED Lamp Installation
- * High Density Polyurethane Insulation(60mm thick) Provides Excellent Low Temperature
- * Invisible Heating Film Protects from water Condensation on the Glass Door
- * Self-Diagnostic and Visual & Audible Alarm System :
 - High/Low Working Room Temp Alarm
 - Electric Power Failure Alarm
 - Status of Door Opening Warning Alarm
 - Low Battery for Controller Warning Alarm
 - Password Locking System for Set Temp

Specifications & Ordering information

Spec.	Model	A. Blood Bank Refrigerator		B. Pharmaceutical Refrigerator	
		"BR-100" 105 Lit, Bench Top	"BR-300" 295 Lit, Floor Standing	"PR-100" 105 Lit, Bench Top	"PR-300" 295 Lit, Floor Standing
Medical Device		NIDS Class-II		NIDS Class-I	
Temp Range		2 ~ 10°C			
Shelf (Included)		1 Basket & 2 Drawer Shelf	3 Drawer Shelf	1 Basket & 2 Wire Shelf	3 Wire Shelf
Compressor		1 / 8 HP	1 / 4 HP	1 / 8 HP	1 / 4 HP
Recorder		Built-in Thermal "STEA1005"	Built-in Temp Chart "STEA1001"	Option	
Defrost Heater		300 W, Automatic Defrost and Dehumidify System			
Forced Air Circulation		Turbo Fan with Automatic Stop During Door Open			
Controller & Display		Microprocessor Digital Controller / 4 Digit LED Display			
Door		Outer Door with Glass Window with Safety Door Lock System			
Safety		High / Low Temp Alarm, Electric Current Leakage Breaker			
Material		Internal : Stainless-steel, External : Epoxy Powder Coated-steel			
Dimension (w×d×h), (mm)	Interior	465×420×h630	560×660×h800	465×420×h630	560×660×h800
	Exterior	560×640×h900	685×865×h1490	560×640×h900	685×865×h1490
	Packing	720×630×h1050	850×720×h1860	720×630×h1050	850×720×h1860
Net & Gross Weight		65 & 80 kg	170 & 185 kg	65 & 80 kg	170 & 185 kg
Power Consumption		100 W	195 W	100 W	195 W
Electric Reqt.s.		110V, 60Hz or 220V, 50/60Hz, 1 Phase			
Cat. No.	220V	DH.RefB0100	DH.RefB0300	DH.RefP0100	DH.RefP0300
	110V	DH.RefB0101	DH.RefB0301	DH.RefP0101	DH.RefP0301
Price, Each. ₩					

* Other Specifications are available upon Customer's Request.

※ 운임 별도!

Spare STS Drawer Shelf or Teflon-coated Steel Wire Shelf & Basket

- DH.RefA0001 (1) STS Drawer Shelf, w415×d340 mm, for "BR-100"
- DH.RefA0002 (1) STS Drawer Shelf, w520×d560 mm, for "BR-300"
- DH.RefA0005 (2) Teflon-coated Wire Shelf, w440×d350 mm, for "PR-100"
- DH.RefA0006 (2) Teflon-coated Wire Shelf, w590×d470 mm, for "PR-300"
- DH.RefA0010 (3) Teflon-coated Wire Basket, w440×d340×h175 mm, for "BR/PR-100"

Optional Accessory

- DH.SteA1001 (4) Temp Chart Recorder, "STEA1001", with "STEA1002" Chart Paper
- DH.SteA1002 Chart Paper, "STEA1002", 52 Chart, for 7 day Recording
- DH.SteA1003 Replacement Pen, "STEA1003", Gea Red Color, for "STEA1001"
- DH.SteA1005 (5) Thermal Printer, Paper Roll, "STEA1005"
- DH.SteA1006 Thermal Paper Package, 4 Paper Roll, for "STEA1005" for "PR"&"BR"
- DH.SteA1010 Mobile Alarm System, "STEA-Mobile"

Refrigerator with Validation (IQ, OQ) Service

- DH.RefB5100 Validation Service(IQ, OQ), with "BR-100"
- DH.RefB5300 Validation Service(IQ, OQ), with "BR-300"
- DH.RefP5100 Validation Service(IQ, OQ), with "PR-100"
- DH.RefP5300 Validation Service(IQ, OQ), with "PR-300"

