

DAIHAN® Digital General Purpose Water Bath "WB", Digital Fuzzy Control System, 6·11·22 Lit, up to 100°C, ±0.1°C
With Stainless-steel Flat Lid, Back Light LCD, with Certi. & Traceability, 정밀 범용 항온수조, 디지털 퍼지 제어 시스템, 스테인리스 스틸 리드 포함



Digital Precise Water Bath, 11Lit, "WB-11"

- CE Certified
- PL(Product Liability) Insurance
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Digital Fuzzy Control System Implementing Superior Temperature Accuracy
- Patented Jog-Shuttle Control System and Digital LCD with Back-Light Function
- * User's Self-Compensation Function to Control Difference between Real Temperature and Indicated Temperature (±10.0°C).
- * 304 Stainless-steel Bath & Lid for Superior Durability & High Thermal Efficiency/Constant.
- * Digital Timer Function(99hr 59min) : 'Delay Time' and 'Operation Time' can be Controlled.
- * Storage Function for the Set Values of Temperature and Timer.
- * Locking Mode Supported for Experimental Safety (Input to Jog-Shuttle can be Disabled).


Specifications & Ordering information

Spec.	Model	"WB-6" Max. Capa. 6Lit	"WB-11" Max. Capa. 11Lit	"WB-22" Max. Capa. 22Lit
Capacity		6 Lit	11 Lit	22 Lit
Temp. Range & Accuracy		Room Temp. +5°C~100°C, ±0.1°C		
Temp. Resolution		0.1°C-Display, 0.1°C-Control		
Temp. Uniformity & Probe		±1.0°C, PT100		
Heating Power		800 W	1 kW	2 kW
Timer & Alarm		99hr 59min (Delay & Continuous run), Error status & Timer-end		
Display		Digital LCD with Back-Light Function		
Controller		Digital Fuzzy Controller with Jog - Shuttle Switch (Turn + Push)		
Safety Circuit		Over-Temp. / -Current protection, Sensor Error Detection		
Material		Stainless-steel (# 304)-Internal, Powder Coated steel-External		
Lid		included Stainless-steel Flat Lid, Optional Dome Lid		
Drain Valve		None		Mounted(φ9.5~11mm)
Dimension (w×d×h)	Effective Space	300×155×h110mm	302×240×h110mm	500×295×h110mm
	Internal	300×155×h150mm	302×240×h150mm	500×295×h150mm
	External	325×180×h260mm	325×265×h260mm	535×330×h260mm
Packing Size (mm) and Gross Weight (kg)		350×210×h310mm, 8 kg	350×300×h310mm, 10 kg	570×360×h310mm, 14 kg
Electrical Reqtts.		1 Phase, AC 120V, 60Hz or AC 230V, 50 / 60Hz		
Cat. No.	230V	DH.WB000106	DH.WB000111	DH.WB000122
	120V	DH.WB000206	DH.WB000211	DH.WB000222
Price, Each. ₩				

* Other Specifications are available upon Customer's Request.



(1) Flat Lid, Stainless-steel (Included)



(2) Dome Lid, Stainless-steel



(3) "BFC106"
Lid with Concentric Ring Cover Sets for 6Lit



(4) "BFC111"
Lid with Concentric Ring Cover Sets for 11Lit



(5) "BFC122"
Lid with Concentric Ring Cover Sets for 22Lit Bath



(6) Test Tube Rack, Stainless-steel

Optional Lid and Tube Rack, Stainless-steel

DH.WB010206	(2) Dome Lid, for 6 Lit, 324×176×h100mm, "BD206"
DH.WB010211	, for 11 Lit, 324×263×h100mm, "BD211"
DH.WB010222	, for 22 Lit, 533×328×h100mm, "BD222"
DH.WB030106	(3) Lid with 2× Concentric Ring Cover Sets, for 6 Lit, Stainless-steel, 330×182×h20mm, "BFC106"
DH.WB030111	(4) Lid with 2× Concentric Ring Cover Sets, for 11 Lit, Stainless-steel, 329×269×h20mm, "BFC111"
DH.WB030122	(5) Lid with 6× Concentric Ring Cover Sets, for 22 Lit, Stainless-steel, 539×334×h20mm, "BFC122"
DH.WB020106	(6) Tube Rack, for 6 Lit, 36Hole×φ17mm, "BTH106", Stainless-steel, 220×125×h78.5mm
DH.WB020206	(6) Tube Rack, for 6 Lit, 15Hole×φ32mm, "BTH206", Stainless-steel, 220×125×h78.5mm
DH.WB020111	(6) Tube Rack, for 11 Lit, 63Hole×φ17mm, "BTH111", Stainless-steel, 220×205×h78.5mm
DH.WB020211	(6) Tube Rack, for 11 Lit, 25Hole×φ32mm, "BTH211", Stainless-steel, 220×205×h78.5mm

Ea. Price, ₩

Water Bath with Validation (IQ, OQ) Service

DH.WB040106	Validation Service(IQ, OQ), with "WB-6", "BV106"
DH.WB040111	, with "WB-11", "BV111"
DH.WB040122	, with "WB-22", "BV122"

Ea. Price, ₩