
DAIHAN® Homogenizer with Direct Controller "HG-15A", up to 27,000 rpm, 1~2,500㎡ With Analog Stepless Control System, High Efficiency Dispersing Tools, High-Speed · High-Quality · Low Noise 균질기 / 호모게나이저, 아날로그 컨트롤러 내장, 초고속/저소음 모터



A. Homogenizer Package-set "HG-15A-Set-A"







■ CE Certified ■ PL(Product Liability) Insurance

- with Certificate & Traceability: Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Useful for All Dispersing and Homogenizing Applications
- Over Heat Protection
- \* Designed for Liquid and Tissue Samples
- \* Useful for All Dispersing and Homogenizing Applications
- \* High Speed / High Quality / Low Noise : Max. 27,000 RPM (without load)
- \* Speed & Power Control Optimized for a Sample
- \* High Efficiency Dispersing Tool made of Stainless-steel and PTFE

## Specifications & Ordering information

| Spec.                         | Model | A. "HG-15A-Set-A"<br>with HT1018  | B. "HG-15A-Set-B"<br>with HT1025                             | C. "HG-15A"<br>(Unit Only) |
|-------------------------------|-------|---|--|----------------------------|
| Speed Range & Adjustment      |       | Max. 27,000 rpm (without load), Stepless  |  |                            |
| Working Range                 |       | 1 ~ 2,500ଲℓ   |  |                            |
| Motor Rating (Input / Output) |       | Input: 300W, Output: 160 W  |  |                            |
| Controller                    |       | Analog Phase Controller   |  |                            |
| Standard Component Acc.       |       | "HT1018" Dispersing Tool,<br>"CL200" Clamp,<br>"ST110" Stand  | "HT1025" Dispersing Tool,<br>"CL200" Clamp,<br>"ST110" Stand | Unit Only                  |
| Safety Device                 |       | Over Heat Protector   |  |                            |
| Usable Dispersing Tool        |       | $\phi$ 8mm Stator "HT1008", $\phi$ 10mm Stator "HT1010", $\phi$ 18mm Stator "HT1018", $\phi$ 25mm Stator "HT1025" |  |                            |
| Material                      |       | Aluminum Die-casting and ABS-Unit, Stainless-steel (#304)-Tool  |  |                            |
| Permissible Temp. & Moisture  |       | Ambient +5 ~ 50°C, 85%  |  |                            |
| Extension Arm Size            |       | Φ12.7×L250mm  |  |                            |
| Dimension & Weight            |       | 60×75×h215mm, 2.5kg   |  |                            |
| Packing Size & Gross Weight   |       | 320×300×h190mm, 5 kg  |  |                            |
| Power Consumption             |       | 160W  |  |                            |
| Electrical Reqts.             |       | 1 Phase, AC 120V, 60Hz or AC 230V, 50 / 60Hz  |  |                            |
| Cat. No.                      | 230V  | DH.WHG02016   | DH.WHG02017  | DH.WHG02015                |
|                               | 120V  | DH.WHG01016   | DH.WHG01017  | DH.WHG01015                |

<sup>\*</sup> Other Specifications are available upon Customer's Request.

## Spare Dispersing Tool & Clamp & Plate Stand

DH.WHG02108 (1) Dispersing Tool, "HT1008",

DH.WHG02110 (2) Dispersing Tool, "HT1010",

Rotor Ø 7.96, Stator Ø 10mm, 1~1,000mℓ

DH.WHG02118 (3) Dispersing Tool, "HT1018",

Rotor Φ 12.8, Stator Φ 18mm, 10~10,000 ml

DH.WHG02125 (4) Dispersing Tool, "HT1025",

Rotor  $\phi$  20 , Stator  $\phi$  25mm, 50~25,000m $\ell$ Clamp, "CL200", for Stirrer or Homogenizer,

SL.Cla8011 Clamp, "CL200", for Stirrer or Homogenizer,
Cast Aluminum, Grip Capacity \$\phi\$ 23mm for Stand/Rod

DH.WOS501510 Standard Plate Stand, "ST110", for Stirrer or Homogenizer,

φ16×h800 mm Rod, w20×d35 cm Plate, with Silicone Pad

DH.WOS501515 Wide Plate Stand, "ST120", for Stirrer or Homogenizer,

φ23×h1,000 mm Rod, w30×d40 cm Plate, with Silicone Pad

<sup>\*</sup> See page 556 for the Specifications of Dispersing Tools and Accessories.