

TECHNICAL DATA

# Fluke Networks Pro3000™ Probe



## Key features

- Loud speaker makes the tone easy to hear through enclosures
- Easy-to-use adjustable volume control dial
- "Quick-twist" tip for easy replacement
- Replacement probe tip stores in battery compartment
- Recessed on/off button

## Product overview: Fluke Networks Pro3000™ Probe

The Pro3000™ unfiltered probe, for use on inactive networks, features a loud speaker to hear tone clearly through walls, enclosures and in loud environments. The recessed on/off button helps prevent the probe from accidentally being turned on when stored.

## Specifications: Fluke Networks Pro3000™ Probe

User interface	ON/OFF push button Volume dial Replaceable tip 3.5 mm earphone jack
Battery	9V alkaline
Temperature	Operating: -20° C to 60° C, Storage: -40° C to 70° C



Case dimensions	9.8 in. x 1.6 in. x 1.3 in. (24.9 cm x 4.1 cm x 3.3 cm)
-----------------	---

## Ordering information



### 26100900

The Pro3000™ unfiltered probe, for use on inactive networks, features a loud speaker to hear tone clearly through walls, enclosures and in loud environments. The recessed on/off button helps prevent the probe from accidentally being turned on when stored.

Includes:

- Pro3000™ Analog Probe

### Optional accessories

### Description

**Fluke Networks Pro3000™ Replacement Tip** [Replacement tip for Pro3000/3000F series probes.](#)



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2022 Fluke Corporation.  
Specifications subject to change without notice.  
09/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**