

Dc Resistance Tester



Product Features

- Blue LCD display
- Chinese menu operation
- Four wire Kelvin cable
- Basic Accuracy 0.05%

	HC-2512	HC-2512A	HC-2512B
Basic Accuracy	0.05% ±2	0.05% ±2	0.1% ±2
Test Range	1uΩ-2MΩ	10uΩ-500kΩ	1uΩ-50kΩ
Test current	1A/100mA/10mA/1mA/ 100uA/10uA/1uA	1A/100mA/10mA/1mA/ 100uA/10uA	1A/100mA/10mA/1mA/ 100uA/10uA
Test gear	5mΩ/50mΩ/500mΩ/5Ω/50Ω/ 500Ω/5KΩ/50KΩ/2MΩ	50mΩ/500mΩ/5Ω/50Ω/ 500Ω/5KΩ/500KΩ	5mΩ/50mΩ/500mΩ/5Ω/ 50Ω/500Ω/5KΩ/50KΩ
Resolution	0.1uΩ	1uΩ	0.1uΩ
Test speed (t/ms)	Fast: 55t/sec, Medium: 66t/sec, Slow: 77t/sec		
Comparator	High or low limited, Speaker		
Trigger mode	Single / Continued		

Comprehensive

Power	Input 220V AC ±10%
Temp.	-10℃~-40℃
Humidity	RH≤75%
Power consumption	Max 30W
Weight	About 5KG
Size	320mm*280mm*100mm

Purchase information

HC-2512	Dc Resistance Tester
HC-2512A	Dc Resistance Tester
HC-2512B	Dc Resistance Tester
FX-1020	Kelvin cable

