

Shaking Rotator

>>> KJMR-III Multifunction Mixer

Features:

- Three mixing models, Adapted to mixing of Blood samples, Urinary samples, Injectables and plasma etc.
- High performance & low noise stepping DC motor to make rapid and thorough mixing of samples.
- Specified silicon clip ring, can fit various kinds of test tubes and centrifuge tubes.
- Tight and reasonable structure makes it running stable. Adapted to various environment.
- LCD with backlight can display the current speed, time and operation mode, convenient for reading and setting.
- Precise digital time and speed setting can easily carry out the continuous operation mode.
- Light touch panel design makes operation easy.



NO.1 working plates:
adapted to Ø12/Ø13/Ø16 test tubes and
1.5ml-15ml centrifuge tubes.



NO.2 working plates:
adapted to Ø12/Ø13/Ø16 test tubes and
1.5ml-50ml centrifuge tubes.

Technical Data:

Operation method:	Rotation: 360°clockwise 360°anticlockwise 360°clockwise-anticlockwise cross Shaking: Forward-backward reciprocating action with < 5°angle Vortex: Forward-backward reciprocating action with < 5°angle+360°clockwise rotation
Speed range:	5-40rpm
No.1 working plate:	1.5ml~15ml test tube or centrifuge tube 22pcs
No.2 working plate:	50ml centrifuge tube 6pcs, 1.5ml~15ml test tube or centrifuge tube 4pcs
Running mode:	Timing
Timing range:	1min-60h
Input voltage(frequency):	AC 220V±10% (50/60Hz)
Input power:	15W
Protective class:	IP31
Permissible ambient temperature:	5-50°C
Permissible relative moisture:	80%
Dimensions:	380×182×190mm
Net. Weight:	3 kg