

Hand wheel Stainless Steel Vertical Pressure Steam Sterilizer

Feature:

1. Hand Wheel structure
2. Automatic Control of sterilization cycle program.
3. Digital window displays the status of work.
4. Temperature can be set 50 Deg.C~126°C
5. Arbitrary time 0~99 Hours
6. Vent Excess pressure from the 0.145~0.165 Mpa
7. The end of steam sterilization without efflux phenomenon
8. Sterilization automatically shut down after the end of buzzer to remind
9. Steam-water inner circulation system: No steam discharge, and the environment for sterilizing will be clean and dry.(It is optional function for LDZX-50KBS and LDZX-75KBS)

Spec:

	Model		
	LDZX-30KBS	LDZX-50KBS	LDZX-75KBS
Volume	30L	50L	75L
Power Supply	220V		
Power	3.0KW	3.5KW	3.5KW
Sterilization chamber Size (mm)	≤350*330	Φ350*520	Φ370*650
Sterilize temperature	50~126°C		
Sterilize time range	0~99 Hours		
Gross weight	65Kg	105Kg	98Kg



Intelligent Stainless Steel Vertical Pressure Steam Sterilizer

Feature:

1. LCD display.
2. Whole stainless steel structure.
3. Intelligent automatic control procedure for sterilization cycle.
4. One key set temperature and time.
5. Over pressure release at 0.217 Mpa
6. Ratory door open structure
7. Safery interlock.
8. Safe protection of water lacking
9. Automatic shutdown with beep reminding after sterilization
10. steam-water inner circulation system: No steam dischage. (Optional)
11. Vacuum drying system (Optional)
12. Printing funtion (Optional)

Spec:

	Model		
	LDZX-40KCS	LDZX-60KCS	LDZX-80KCS
Volume	40L	60L	80L
Power Supply	220V		
Power	3.5KW	3.5KW	3.5KW
Sterilization chamber Size (mm)	≤370*380	Φ370*560	Φ370*750
Sterilize temperature	50~134°C		
Sterilize time range	0~99 Hours		
Gross weight	95Kg	105Kg	120Kg

