



## LS-B35/50/75/100L-I-Automatic (Digital Display Automatic Autoclave)

### Characteristics:

1. Fully stainless steel structure.
2. Hand wheel type of quick-open door structure.
3. Door safety lock system.
4. Digital display of working status, touch of key.
5. Auto discharge the cool air, and steam discharging automatically after sterilization.
6. Over temperature & over pressure auto-protection.
7. Safe protection of water lacking
8. Self-inflating type seal.
9. Automatically shut off with beep reminding after sterilization
10. With two stainless steel sterilizing baskets

### Specification:

Model	LS-B35L-I-Automatic	LS-B50L-I-Automatic	LS-B75L-I-Automatic	LS-B100L-I-Automatic
Valid volume	35L(φ318*450mm)	50L(φ340*550mm)	75L(φ400*600 mm)	100L(φ440*650 mm)
working pressure	0.22MPa			0.14 MPa
Working temperature	134°C			126°C
Max working pressure	0.23 Mpa			0.165 Mpa
Heat average	± 1°C			
Timer	0~99min or 0~99hour59, in			
Adjustment of temperature	105~134°C		105~126°C	
Power	2.5Kw/AC220V 50Hz	3Kw/AC220V 50Hz	4.5Kw/AC220V 50Hz	
Overall dimension (mm)	450*450*1010	510*470*1130	560*560*1120	540*560*1250
Transport dimension(mm)	570*550*1150	590*590*1280	650*630*1280	630*650*1370
G/N. W:	72Kg/56Kg	88Kg/68Kg	100Kg/ 80Kg	110Kg/ 85Kg