

Thermo-9816/9866/98501/9891 Digital Hygro Thermometer/Portable Thermometer

Product Description

- Stainless steel probe, line measurements.
- Wide measuring range, °C and °F direct conversion, data hold, maximum and minimum display function, etc.
- Maximum and minimum temperature °C / ° F range selectable at any time.

Model	Thermo-9816	Thermo-9866	Thermo-98501	Thermo-9891
Measuring range	-50°C~125°C (-58°F~257°F)	-50°C~125°C (-58°F~257°F)	-50°C~125°C (-58°F~257°F)	-50°C~125°C (-58°F~257°F)
Resolution	0.1°C/°F	0.1°C/°F	0.1°C/°F	0.1°C/°F
Accuracy	±1°C or ±2°F (at 0.0°C~80°C) ±2°C or ±4°F (at -50°C~0.0°C, 80°C~125°C)	±1°C or ±2°F (at 0.0°C~80°C) ±2°C or ±4°F (at -50°C~0.0°C, 80°C~125°C)	±1°C or ±2°F (at 0.0°C~80°C) ±2°C or ±4°F (at -50°C~0.0°C, 80°C~125°C)	±1°C or ±2°F (at 0.0°C~80°C) ±2°C or ±4°F (at -50°C~0.0°C, 80°C~125°C)
Battery Type	1 x 1.5V	1×1.5V (AAA Battery)	1.5V×1 AG13	1.5V×1 AG13
Dimensions	155×48×22(mm3)	130 × 65 × 24	175 × 57 × 25	150 × 29 × 20