

- 1) Interior of the bath is made of stainless steel with a beautiful and novel appearance.
- 2) Digits display, Microprocessor control with timing function.
- 3) Audible and visible tracking alarm indicates over temperature, which provides samples reliable protection.

Option: intelligent programmable LCD temperature controller

Specification:

Model	Heating Bath	Heating Bath(interior and exterior are all made of stainless steel)	Heating Circulating Bath (With electromagnetic-pump)	Transparent Viewing water Bath	3 Holes heating water bath
	CU-420	DK-8AXX	DKB-600B	TS-030	DK-8D
	CU-600	DK-8AX DK-8AD	DK-8AB		
Electrical Requirements	AC 220V 50HZ				
Input Power	500W/1000W	400W 600W 1000W	1000W	1100W	750W

Temperature Range	RT 5~99°C		RT 5~70°C		RT 5~99°C
Temperature Stability	±0.5°C		±0.3°C		
Temperature Resolution	0.1°C				
Chamber Capacity	11L 34L	12L 22L 30L	22L 30L	27L	2.1L*3
Interior Dimension(mm) W*D*H	420*180*150 600*300*190	300*240*160 450*300*160 600*300*160	500*300*150 600*300*170	300*300*300	150*125*110
Overall Dimension(mm) W*D*H	570*220*260 750*350*300	460*280*190 610*340*190 760*340*190	660*340*200 770*370*280	480*370*380	490*245*310
Timing Range	1~9999min				