

Pocket DL Leeb Hardness Tester



Introduction:

- New Leeb hardness tester MH-500DL with durable metal housing.
- It still used the patent dual-coil technology which makes it to have extraordinary accuracy: $\pm 4\text{HL}$ with high contrast color TFT display and durable metal housing.
- It has a moving bar-graph display which can evaluate the workpiece upon deviation value by different color for easy visual distinguish.
- It can download measuring data to PC and printout to micro-printer by USB port and wirelessly with internal wireless module.
- The battery can be charged simply from USB port, also it has a customer re-calibration and statistics function.

Features:

- Integrated design, easy operation
- Four display styles

- Durable metal housing mode
- TFT320*320 color display
- Wide operation environment: -20°C-70°C menu language
- High accuracy: +/-4HL (or 0.5% @HLD800)
- Auto compensate error for different impact direction computer by USB or Bluetooth
- Moving bar-graph display Bluetooth interface, it can connect micro-printer wirelessly
- Two evaluation modes: By limit / Deviation rechargeable battery, it can be charged by USB or power source
- Two Calibration modes: Coincident / Independent can be calculated automatically
- With strength conversion value automatically or manually
- Packed in rigid carrying case
- Multi-printing
- Sound reminder
- Up to 10 kinds of
- DL probe
- It can connect to
- USB and
- 3.7 V Li-ion
- Statistics value
- Power on / off

Specifications:

Product Name	Pocket DL Leeb Hardness Tester
Model	MH-500DL
Code#	852-156DL
Accuracy	±0.5% @ HL=800 / ±4HL
Display	High contrast color TFT 320*320
Hardness scale	HL / HRC / HRB / HB / HV / HS / HRA / ob
Measuring range	HL100~960 / HRC0.9~79.2 / HRB1.2~140/ HB1~1878/ HV1~1698 / HS0.5~128/ HRA7~88.5 / ob(rm)24~6599N/mm2
Probe	DL probe
Materials and curves	11 common metal materials, 75 curves
Memory	30/60 files on request, 100 data for each file, can be saved and re-readable
Statistics function	Average /Max. /Min. /Single Value
Re-calibration	Coincident /Independent
Indicator	Low battery
Language	English, Chinese, Russian, Korean, French, Italian, German, Turkish, Spanish
Interface	USB/Bluetooth to PC for transferring data, wireless printing, USB for charging
Power on/off	Auto/Manual
Power supply	3.7V Li-ion rechargeable battery
Working environment	-20°C~+70°C
Dimension (mm)	205x44x22
Net weight (g)	120
Standards	Conforming to ASTM A956, DIN 50156, GB/T 17394-1998