



分享到 :



30KN / 50KN Digital Display Electronic Universal Testing Machine Machine

Product description:

30KN / 50KN Digital Display Electronic Universal Testing Machine Machine 1. Application It is applicable for wide range of material for tension, compression, bending, shearing and low cycle test. Suit

(<https://www.facebook.com/Testing-machine-1867923476851664/>)

Choose language



(<http://www.hssdgroup.com/PRODUCT/TorsionTestingMachine26.htm>) (<http://www.hssdgroup.com/PRODUCT/CompressionTestingMachine27.htm>) (<http://www.hssdgroup.com/PRODUCT/BroachingMachine34.htm>) (<http://www.hssdgroup.com/PRODUCT/BroachingMachine35.htm>)

Share With:

We're here to help:
Easy ways to get the answers you need.

Send E-mail (<mailto:Louis@hssdtest.com>)

Chat Now (<skype:sales02@hssdtest.com?chat>)

PRODUCT DETAILS

PRODUCT VIDEO

30KN / 50KN Digital Display Electronic Universal Testing Machine Machine



1. Application

It is applicable for wide range of material for tension, compression, bending, shearing and low cycle test. Suitable for metal, rubber, plastic, spring, textile and components testing. It is widely used in the industries, research and development, test institutes and training centers etc.

Choose language ▼



ISO 9001:2015, ISO6892, ISO7438, ISO7500-1, EN10002-4, GB/T228-2002, GB 16491-2008, HGT 3844-2008, GB 16491-2008, HGT 3844-2008, GB6349-1986, GB/T 1040.2-2006, ASTM C165, EN826, EN1606, EN1607, EN12430 etc.

3.Specifications

Model	WDS-30	WDS-50
Structure	Four-column floor or desk model, (upper is compression and lower is tensile)	
Max. Load(kN)	30	50
Load accuracy	ISO 7500 Class 1	ISO 7500 Class 1
Load range	2% ~ 100%F·S	2% ~ 100%F·S
Load resolution	1/ 50000	
Resolution of displacement	0.01mm	
Test speed(mm/min)	0.05-1000 stepless arbitrary setting	
Speed accuracy	within ±1% / ±0.5% of set speed	
E-Tensile space(mm)	700 (can be customized)	
E-Compression space(mm)	700 (can be customized)	
D-Test width(mm)	500 (can be customized)	
F-Beam travel distance(mm)	1050	
H-Workbench thickness(mm)	58	
I-Base height(mm)	435	
Power supply	AC220V±10% , 50Hz/60Hz(can be customized)	
Video show	https://youtu.be/1QtovStGXbl (https://youtu.be/1QtovStGXbl)	