500KN/600KN Computer Control Electronic Universal Testing Machine

Product description:

1. Application It is applicable for wide range of material for tension, compression, bending, shearing and low cycle test. Suitable for metal, rubber, plastic, spring, textile, and components testing

(http://www.hssdgroup.com/PRODUCT/Hydraulic-Compression-Testing-Machine/1876851664/)

Choose language

HST GROUP

Focus In Material Test

(http://www.hssdgroup.com/PRODUCT/Ha

(http://www.hssdgroup.com/PRODUCT/Ha

(http://www.hssdgroup.com/PRODUCT/Ha

(http://www.hssdgroup.com/PRODUCT/Ha

Share With:

We're here to help:
Easy ways to get the answers you need.

Send E-mail (mailto:Louis@hssdtest.com)

Chat Now (skype:sales02@hssdtest.com?chat)

PRODUCT DETAILS

PRODUCT VIDEO

1. Application

It is applicable for wide range of material for tension, compression, bending, shearing and low cycle test. Suitable for metal, rubber, plastic, spring, textile, and components testing. It is widely used in the corresponding industries, researc h and development, test institutes and training centers etc.

2. Standards

ASTMA370, ASTME4, ASTME8, ASTME9, ISO6892, ISO7438, ISO7500-1, EN10002-4, GB/T228-2002, GB 16491-2008, HGT 3844-2008 QBT 11130-1991, GB13-22-1991, HGT 3849-2008,GB6349-1986, GB/T 1040.2-2006, ASTM C16 5, EN826, EN1606, EN1607, EN12430 etc.

3. Specifications

Model	WDW-500/600/500E/600E
Max. Load(kN)	500 / 600
Load accuracy	Class 1 / Class 0.5
Load resolution	1/300000
Resolution of deformation	0.04um
Accuracy of displacement	Within±0.5%of indicating load
Resolution of displacement	0.01mm
Test speed(mm/min)	0.05-200 stepless arbitrary setting
Speed accuracy	Within ±0.5% of set speed
E-Tensile space(mm)	1000 (can be customized)
E-Compression space(mm)	850 (can be customized)
D-Test width(mm)	800 (can be customized)
F-Beam travel distance(mm)	1150
H-Workbench thickness(mm)	108
I-Base height(mm)	540-970 adjustable
Power supply	AC380V/220V±10% , 50Hz/60Hz (can be customized)
Weight(KG)	4300