



home (/) > Product (/products.html) > Security and Fire Protection (/Security.html) > IRS-FB432-T (/)

IRS-FB432 (/IRS-FB432.html) IRS-FB432-T (/IRS-FB432-T.html) IRS-FB462 (/IRS-FB462.html) IRS-FB462-T (/IRS-FB462-T.html) IRS-PT264 (/IRS-PT264.html)

IRS-PT4F4 (/IRS-PT4F4.html) XSENTRY (/xsenry.html)

Temperature Measurement Dual-spectrum Intelligent Thermal Imaging Bullet Camera

IRS-FB432-T is a network thermal camera for security and monitoring that integrates thermal camera and visible light camera. The thermal camera resolution is up to 110,000 pixels and the visible light camera resolution is up to 2,000,000 pixels.

Thermal camera resolution: 384×288

Pixel pitch: 17μm

Visible light camera resolution: 1920×1080

Applicable scenarios: Electric temperature measurement, Forest fire prevention, Warehouse fire prevention, Industrial temperature measurement.

Product Features

Adopting the new generation of InfiRay 17μm uncooled infrared detectors to see farther and clearer.

High-definition dual-spectrum imaging, with a maximum thermal resolution of 110,000 pixels and a visible light resolution of 2,000,000 pixels.

Support independent temperature measurement with built-in professional temperature measurement analysis tools and multiple linkage alarm rules.

Support intelligent behavior analysis such as regional intrusion and tripwire intrusion.

Support intelligent smoke and fire detection.

Support ONVIF and GB28181 protocols.

IP66 protection.

Model	IRS-FB432-T	
Thermal Camera Specifications		
Detector Type	VOx Uncooled IRFPA detector	
Max. Image Size	384×288	
Pixel Pitch	17μm	
Spectral Band	8~14μm	
NETD	≤40mk (@25°C, F#=1.0)	
Focal Length	9.7mm	13mm
FOV	37.9°×28.7°	20.1°×15.1°
IFOV	1.753mrad	1.308mrad
Color Palette	Black hot/White hot/Iron red/Rainbow/... Various palettes optional (18 modes in total)	

Dual-spectrum Fusion	Support dual-spectrum fusion enhancement
Visible Light Specifications	
Sensor	1/2.7" 2,000,000-pixel high-performance CMOS
Resolution	1920×1080
Focal Length	6mm
White Balance	Support
Day-night Switching	IR-CUT auto switching
Digital Denoising	3D denoising
Light Compensation Function	Infrared compensation, range> 30m
Network Parameters	
Network Protocols	TCP,UDP, ICMP,RTP,RTSP,DHCP,PPPOE,UPNP,DDNS, ONVIF,802.1x,FTP
Synchronized preview channels	6
User Rights	Three levels of user rights: administrator, senior operator, user
Safe Mode	Authorized user name and password
Video Compression Standard	H.264/H.265
Audio Compression Standard	G.711u/ G.722
Video Parameters	
Max. Image Size	1920×1080 (visible light camera)
	384×288 (thermal camera)
Main Stream Image	Visible Light Camera:
	50Hz: 25fps (1920×1080), 25fps (1280×720)
	60Hz: 30fps (1920×1080), 30fps (1280×720)
	Thermal Camera:
	50Hz: 25fps (384×288)
	60Hz: 30fps (384×288)
Sub stream Image	Visible Light Camera:
	50Hz: 25fps (704×576), 25fps (352×288)
	60Hz: 30fps (704×480), 30fps (352×240)
	Thermal Camera:
	50Hz: 25fps (384×288)
	60Hz: 30fps (384×288)
Intelligent Functions	
Fire Point Detection	Support
Accurate Temperature Measurement	Measuring range: -20°C ~+550°C, Accuracy: ±2°C or ±2% (the larger one prevails)
Abnormal Temperature Alarm	Support high/low/AVG temperature limit and other temperature measurement rules
Intelligent Alarm	Support linkage alarm of network cable break, IP address conflict, memory full, memory error

Intelligent Detection	Cross border detection, entry detection, exit detection, and abandoned object detection
System Integration	
Communication Interface	One RJ45 10M / 100M self-adaptive, one RS485
Audio Input	1 linear input
Audio Output	1 linear output
Alarm Input	2 channels
Alarm Output	1 channel
Video Output	1 analog video output, supporting CVBS
Storage Interface	Support Micro SD card (up to 64G)
General Specifications	
Operating Temperature and Humidity	-40°C~+70°C, RH<95%
IP Grade	IP66
Power Supply	DC12V ±25% / PoE
Power Consumption	≤8W
Size	319.5 mm×121.5 mm×103.6mm
Weight	≤1.8kg

Product consulting

* Message contents :

Please enter your message contents

Mobile phone :

Please enter your mobile phone number

* Country :

Please enter your country

* Product :

Please enter the product you wan

E-mail :

Please enter your E-mail

Submit

CONTACT US

(/contact.html)

Marketing Dept.Email:sales@infray.com

HR Email:hr01@infray.com

Sales Hotline:+86-400-998-3088 (tel:+86-400-998-3088)

After sales hotline:+86-400-883-0800 (tel:+86-535-3410669)

Address:11th Guiyang Street, YEDA,Yantai 264006,P.R.China

IMAGERS

[Thermal Monocular \(/eyethermalmonocular.html\)](#)

[Phone Thermal Camera \(/T2thermalcamera.html\)](#)

[Car Thermal Camera \(/AsensMthermalcamera.html\)](#)

[Clip on Thermal Scope \(/clipcthermalscope.html\)](#)

[Rico Thermal Scope \(/Rico.html\)](#)

[Tube Thermal Scope \(/Tube.html\)](#)

[Dual spectrum thermal imager \(/xfusethermalimager.html\)](#)

[online monitring thermal camera \(/A8thermalcamera.html\)](#)

MODULES

[Micro III Thermal Imaging Module \(/Micro3thermalmodule.html\)](#)

[Mini Thermal Imaging Module \(/Mini.html\)](#)

[LT Temperature Measurement Module \(/LTthermalmodule.html\)](#)

[FT Alarming Thermal Imaging Module \(/FTthermalmodule.html\)](#)

[Phoenix Cooled MWIR Imaging Module \(/phoenixthermalmodule.html\)](#)

APPLICATIONS

[Infrared Thermography \(/gycw.html\)](#)

[Security Thermal Camera \(/aqjk.html\)](#)

[Night Vision \(/hwyd.html\)](#)

[UAV Thermal Module \(/wrjzh.html\)](#)

[Smart Phone \(/zhsh.html\)](#)

[Automotive Thermal Camera \(/qcys.html\)](#)

Follow Us:

<https://www.facebook.com/InfiRayHQ>

https://www.instagram.com/infiray_technology/

<https://iraytek.en.alibaba.com/index.html>

<https://www.linkedin.com/company/22301729/>

https://www.youtube.com/channel/UC6_A8T1QPf07hciH711s7Ug

<https://twitter.com/InfiRay>

