

VIEW900

THE MOST RELIABLE & ACCURATE CABLE ANTENNA ANALYZER

- Broadband Frequency Coverage – 5 MHz to 6 GHz
- Multi-Functions - Return Loss, VSWR, Cable Loss, Distance-To-Fault, Smith Chart
- Compact, Lightweight Hand-held Design - 2.1 Kg (4.63 lbs)
- 5.5 hours of long battery lifetime for daily job
- Easy-To-Operate, Intuitive GUI
- 7" Wide and Sunlight Viewable Bright Color LCD



BELIEVE
YOUR
EYES

VIEW900 HIGHLIGHTS




USB -
Port for external USB devices, memory stick, e-calibrator and RF power sensors.

Ethernet -
For internal debugging purpose.

DC Power -
Connect with an AC/DC adaptor

Type-N(f) RF Out -
1 Port reflection measurement, VSWR/DTF/Cable Loss/Smith Chart



Reflection Measurement -
VSWR, Return Loss, DTF, Cable Loss, Smith Chart



Calibration -
Open-Short-Load Mechanical & Electrical Calibration



7" Touch Screen with Smart GUI High Resolution of 800x480



Power Measurement -
Terminal & Directional Power Sensor



Quick & Easy operation with intuitive GUI

touch

TECHNICAL SPECIFICATIONS

Item	Sub Item	Specification	
General	Max input power	+25 dBm (+33 dBm damage level)	
	Frequency Range	5 MHz to 6 GHz	
	Frequency Accuracy	< ±3 ppm	
	Frequency Resolution	10 kHz	
	Scan Speed	Reflection: < 0.7 ms/point DTF: < 1.0 ms/point	
	Number of Data Points	129, 257, 513, 1025, 2049	
	Display	Single & Dual display	
	Test Port	N-Type Female, 50 Ω	
	Storage	Internal: Minimum 512 MB	
	(Trace / Screen / Setup)	External: Limited by size of USB (32 G)	
VSWR	Return Loss Range	0 to 60 dB	
	VSWR Range	1 to 65	
Cable Loss	Cable Loss Range	0 to 30 dB	
DTF	Return Loss Display Range	0 to 60 dB	
	VSWR Display Range	0 to 65	
	Distance Range	0 to 1,250 m (4,125 ft)	
Interference Immunity	On Frequency	+5 dBm	
	On Channel	+15 dBm	
Miscellaneous	Dimension	272 x 188 x 65 mm (10.7 x 7.4 x 2.55 inches)	
	Weight	2.1 kg (include battery)	
	Voltage and Current	12 VDC, 3.0 A	
	Adaptor	AC Input	100 to 240 V, 1.5 A
		DC Output	12 VDC, 3.0 A
	Battery	Li-ion 7800 mAh (5.5 hr operating time after full charge)	
Environmental	Operating Temperature	-10 °C ~ +50 °C (14 °F ~ +122 °F)	
	Storage Temperature	-40 °C ~ +80 °C (-40 °F ~ +176 °F)	
	Humidity	95 % R.H. No Condensation	

OPTIONAL POWER SENSOR

V90 Terminating Power Sensor	Frequency Range	50 MHz to 6 GHz
	Measurement	Average Power
	Measurement Range	-45 dBm to +10 dBm
	Accuracy	±7 %
	Port	Type-N(f)

VIEW900

ORDERING INFORMATION

STANDARD CONFIGURATION

Model	Description	Part Number
VIEW900	Cable and Antenna Analyzer VIEW900 include: 1. VIEW900 Cable and Antenna Analyzer, 5 MHz to 6 GHz 2. V96 Mechanical Calibration Kit 3. Soft-carrying Case	TM00900
VIEW900B01	VIEW900 Bundle 1 include; 1. VIEW900, TM00900 2. USB A to USB A cable (1.0 m), TM00900900 3. RF cable DC to 8 GHz Type-N(m) to Type-N(f), 1.5 m, TM00900700	TM00900B01

SUPPLIED ACCESSORIES

- Soft-carrying Case for VIEW900
- AC/DC adapter
- Rechargeable Li-Ion battery
- 8 GB USB memory

OPTIONAL ACCESSORIES

Model	Description	Part Number
GPS	USB GPS Receiver and Antenna for View900	TM00900GPS
V90	Terminating Power Sensor, Type N(m), DC to 6 GHz, 50 Ω	TM00090
V95	Electrical Calibration Kit, Type N(m), DC to 6 GHz, 50 Ω	TM00095
V96	Mechanical Calibration Kit, Type N(m), DC to 6 GHz, 50 Ω	TM00096
	Soft-carrying Case for VIEW900	TM00900300
	Backpack carrying case for VIEW900	TM00900301
	VIEW900 Warranty Extension of 1yr for Asia and North America	TM00900100
	VIEW900 Warranty Extension of 1yr for Latin America and EMEA	TM00900101
	VIEW900 Calibration Services for Asia and North America	TM00900200
	VIEW900 Calibration Services for Latin America and EMEA	TM00900201
	USB A to USB A cable (1.0 m)	TM00900900
	RF Cable DC to 8 GHz Type-N(m) to Type-N(f), 1.5 m	TM00900700
	Rechargeable lithium ion battery	TM00900400
	AC/DC adapter	TM00900500



You dream,
we DESIGN

Copyright © 2018 INNO Instrument Inc. All rights reserved.

E-22F, 30, Songdomirae-ro, Yeonsu-gu, Incheon 21990, Republic of Korea
tel 82-32-837-5600 fax 82-32-837-5601

Product specifications and descriptions in this document subject to change without notice.

Printed in Korea

www.innoinstrument.com

Visit us on Facebook

www.facebook.com/innoinstrument