

CONTACT TACHOMETER

CODE 9224-213



wheel with 0.1m
perimeter
(included)



clamping sleeve
(included)



cone head
(included)



small cone head
(included)



cone cavity
head (included)

- Can measure rotary speed, line speed and line length
- Automatically save the maximum value, minimum value and the last value, 96 data can be stored during continuous measurement
- With backlight display



SPECIFICATION

Measuring range	Rotary speed	0.5~19999RPM
	Line speed	0.05~500m/min
	Line length	0.05~99999m
Resolution	Rotary speed	0.1RPM (range 0.5~999.9RPM) 1RPM (range 1000~19999RPM)
	Line speed	0.01m/min (range 0.05~99.99m/min) 0.1m/min (range 100~500m/min)
	Line length	0.02m
Accuracy	Rotary speed	$\pm(0.4\%n+1d)$ RPM ($n<300$ RPM) $\pm(0.05\%n+1d)$ RPM ($n\geq 300$ RPM) n is rotary speed, d is resolution
	Line speed	$\pm(1\%+1d)$ m/min d is resolution
	Line length	$\pm(1\%+1d)$ m d is resolution
Sampling time	0.8s (above 60RPM)	
Operating temperature	0~40°C	
Power supply	3×AA batteries	
Dimension	171×71×35mm	
Weight	162g	

STANDARD DELIVERY

Main unit	1 pc
Wheel with 0.1m perimeter	1 pc
Clamping sleeve	1 pc
Cone head	1 pc
Small cone head	1 pc
Cone cavity head	1 pc
Battery (AA)	3 pcs