

Technical Parameter







Model	2-5C
Max Speed	5000rpm
Max RCF	3013 × g
Max Capacity	6 × 50ml
Timer	1s ~ 99min
Revolutions/min	± 10r/min
Voltage	AC 220 ± 22V 50/60Hz 10A
Power	150W
Noise Level	≤ 62dB (A)
Size	420 × 320 × 265 (mm)
Net Weight	19kg

Product Features

- ◆ Microcomputer control system with HD LCD display, driven by large torque variable frequency motor.
- ◆ Adopts a three-layer special anti-collision protection structure, with special noise reduction technology.
- ◆ Steel structure, centrifugal chamber made of stainless steel with environmental protection anti-corrosion coating, which is corrosion resistant and acid alkali resistant.
- ◆ 10 gear acceleration /deceleration with linear drive.

- ◆ Food grade silicone integrated seal ring, beautiful and durable, high temperature resistant, anti-aging, anti-corrosion, no deformation and cracking.
- ◆ Large capacity storage of 40 sets of program groups. Automatic calculation and display of speed, RCF, time etc.
- ◆ Over-speed, imbalance, door cover protection, over-current, rotor error etc protections.
- ◆ Adopted Ultra-high safety protection with low noise and higher safety.

Rotor Parameters

Rotor NO.	Rotor Pictures	Rotor Capacity (ml)	Max Speed (r/min)	Max RCF (× g)
Angle Rotor				
1		12 × 15ml (W)	5000rpm	2934 × g
2		6 × 50ml (W)	5000rpm	3013 × g
3		12 × 20ml	4000rpm	2250 × g
4		24 × 10ml	4000rpm	2200 × g

* All products can be customized, designed and produced according to customer requirements.