Hunan Kecheng Instrument Equipment Co., Ltd

DT45C Low Speed Table Centrifuge



Product Features:

Intelligent control system

- ◆ Five groups of programs with humanized design.
- ◆ Program group shortcut key, can store 99 groups of program, convenient to call at any time.
- ◆ Automatic electronic door lock.
- ◆ With instantaneous and continuous centrifugation functions.

Excellent kernel performance

- ♦ HD large LCD display and the parameters can be revised during operation without shutdown.
- ◆ Microcomputer control ,AC frequency conversion brush-less motor with fast speed and stable operation.
- ◆ 10 gears acceleration /deceleration with linear drive.
- ◆ Two modes can be set: start timing/arrival revolution timing.

Careful and safe

◆ With rotor automatic identification system .

Address: NO. 602, 6F, C2 Building, JinRong Wangcheng Sci-Tech Industrial Park, NO. 858 Purui West Road, Wangcheng Economic & Technological Development Zone, Changsha city. Hunan province, China

Hunan Kecheng Instrument Equipment Co., Ltd

- ◆ Over speed, over heat, unbalance protections with auto lid lock.
- ◆ Steel Structure, centrifuge chamber made of stainless steel with Environmentally friendly anti-corrosion coating treatment.

Intimate detail design

- ◆ Special noise reduction system.
- ◆ An intimate tool rack is provided for accompanying tools to guard the instrument at all times.
- ◆ With an operation SOP guide map, which makes it easier and more standard for laboratory workers.
- Equipped with rotor lid that can be quickly locked for easy use.

Technical Parameter:

| Model | DT45C | | | | | |
|-----------------|--|-----------------------------|----------------------------------|--|--|--|
| Max Speed | 5500rpm | Power | 1000W | | | |
| Max RCF | 5952×g Noise Level | | ≤ 62dB (A) | | | |
| Max Capacity | 4×750ml Size | | $580 \times 465 \times 395$ (mm) | | | |
| Timer | 1s \sim 99h59min | Net Weight | 61kg | | | |
| Revolutions/min | $\pm 10 \mathrm{r/min}$ | Rotor automatic recognition | Yes | | | |
| Voltage | AC 220 ± 22 V 50 Hz 10 A or custom | / | / | | | |

Rotor parameters:

| Rotor Name | Rotor NO. | NO. | Capacity | Max Speed (r/min) | Max RCF(×g) |
|--------------------|--------------|-----|--------------------------------------|----------------------|----------------------|
| Angle rotor (W) | 1 | 1 | $40 \! 	imes \! 15$ ml | 5500rpm | 5952×g |
| Angle rotor (W) | 2 | 2 | 6×50ml | 5500rpm | 3645×g |
| Swing-out rotor | 3 | 3 | 96×2~7ml (Blood collection tube) | 4000rpm | 3184×g |
| | | 4 | 100×2~7ml (Blood collection tube) | 4000rpm | 3184×g |
| | | 5 | 120×2~7ml (Blood collection tube) | 4000rpm | 3184×g |

Address: NO. 602, 6F, C2 Building, JinRong Wangcheng Sci-Tech Industrial Park, NO. 858 Purui West Road, Wangcheng Economic & Technological Development Zone , Changsha city. Hunan province, China

Email:amy@kc-centrifuge.com Tel: +86-0731-55881818 Website:www.kc-centrifuge.com

Hunan Kecheng Instrument Equipment Co.,Ltd

| Swing-out rotor | | 6 | 4×750ml(Round bucket) | 4000rpm | 3309×g |
|--|---|----|---|------------|----------|
| | 4 | 7 | 4×750ml(Round bucket)/ | 4000rpm | 3309×g |
| | 1 | (| (with biosafety lid) | 40001 pili | 3309 ^ g |
| | | 8 | 4×750ml(Square bucket) | 4000rpm | 3309×g |
| Swing-out rotor | 5 | 9 | 4×500ml(Round bucket) | 4000rpm | 3184×g |
| | | 10 | 4×500ml(Round bucket) (with biosafetey lid) | 4000rpm | 3184×g |
| | | 11 | 4×500ml(Square bucket) | 4000rpm | 3184×g |
| | | 12 | 4×500ml Sharp bucket (Corning tube) | 4000rpm | 3184×g |
| Swing-out rotor | 6 | 13 | 4×250ml(Round bucket) | 4000rpm | 3040×g |
| | | 14 | 4×250ml(Round bucket)/ (with biosafety lid) | 4000rpm | 3040×g |
| | | 15 | 4×250ml(Square bucket) | 4000rpm | 3040×g |
| | | 16 | 4×250ml Sharp bucket (Corning tube) | 4000rpm | 3040×g |
| | | 17 | 6×250ml(Round bucket) | 4000rpm | 3040×g |
| Swing-out rotor body | 6 | 18 | Swing-out rotor body 4×250ml | | |
| Pipe rack | 6 | 19 | 56×5ml (Blood collection) | 4000rpm | 3040×g |
| | | 20 | 16×50ml(Conical/round bucket) | 4000rpm | 3040×g |
| | | 21 | 36×15 ml | 4000rpm | 3040×g |
| Swing-out rotor | 7 | 22 | Micro-plate 4×2×96 hole | 4000rpm | 2763×g |
| Swing-out rotor Square basket | 7 | 23 | Square bucket include: Adapter 4×10× 15ml (conical bottom) Adapter 4×4× 50ml (conical bottom) | 4000rpm | 2763×g |
| Swing-out rotor | 8 | 24 | Micro-plate 2×2×96 hole | 4000rpm | 2057×g |
| Swing-out rotor | 9 | 25 | 4x100m1 | 5000rpm | 4390×g |

Address: NO. 602, 6F, C2 Building, JinRong Wangcheng Sci-Tech Industrial Park, NO. 858 Purui West Road, Wangcheng Economic & Technological Development Zone, Changsha city. Hunan province, China

Email:amy@kc-centrifuge.com Tel: +86-0731-55881818 Website:www.kc-centrifuge.com

Hunan Kecheng Instrument Equipment Co.,Ltd

