Multi-head Ionizing Air Blower Static Eliminator KESD KF-150AR

Product Features

- · Rapidly neutralizes static charges,
- · Smart, delicate, easy to operate,
- · Adjustable continuously to wind speed. indicating lamp for ions producing,
- Small size, light weight and portable,
- With magnetic leakage transformer, long life span and short-circuit proof,
- · Variable speed fan with wide range of air flow,
- · Inherently balanced ion output,
- · Ionization indicator lamp,
- Ion emitter cleaner inside, easy cleaning .



Technical Parameters

Technical parameters		
Product model	KF-150AR	
Input power supply voltage	DC24V	
Destaticizing normal operation indicator light	If destaticizing operation is normal,the green indicato light is on	
Destaticizing abnormal indicator light	If destaticizing operation is abnormal,the red indicator light is on	
Destaticizing time	about 1.3s(200mm place)	
Destaticizing time	about 1.3s(200mm place)	
lon balance	Automatic ion balance system 0±15V	
Air volume	2.97-4.07m³/min(constant air flow)	
Ozone concentration	Below 0.03ppm(distance 150mm)	
Applied environmental temperature	0~40°C(no condensation)	
Applied environmental humidity	30-70% RH (no water drop condensation)	
Overall size /mm	142.6*78*178(exclouding stents)	
Weight	8.02Kg (exclouding stents)	

Anti-static test condi	tion			
Operating voltage:DC	24V Test voltage:	±1000V-±100V Ambier	nt temperature:23°C±2°C	
Distance		300mm	600mm	900mm
Destaticizing time	Positive	1.0s	2.3s	4.0s
	Negative	1.2s	2.8s	4.4s
Residual voltage	Positive	0.104		
	Negative	<u±1uv< td=""><td colspan="3">- <0±10V</td></u±1uv<>	- <0±10V	