

- [Home](#)
- [Products](#)
 - [Electric field meter](#)
 - [EFM 022](#)
 - [EFM 023](#)
 - [EFM 113B](#)
 - [EFM 115](#)
 - [EFM 120](#)
 - [EFM 125](#)
 - [EFM 235](#)
 - [EFM 255](#)
 - [equipment](#)
 - [CPS 022](#)
 - [ZBS 022](#)
 - [EFM 022 ZBS](#)
 - [FMK 1](#)
 - [HMK 40](#)
 - [Tripod mount](#)
 - [Hand electrode MEL](#)
 - [Test lead, teflonized](#)
 - [MK 1](#)
 - [MK 11](#)
 - [MK 11 S2](#)
 - [MK 023](#)
 - [VMS 023 \(BGT\)](#)
 - [SGG 421](#)
 - [ASP 113](#)
 - [UAC 110](#)
- [Charge plate monitors](#)
- [TERA ohmmeter](#)
- [HGB and shoe tester](#)
- [AUDIT SET](#)
- [AUDIT CASE](#)

- [Prices](#)
- [Support](#)

[Products](#) > [Electric field meter](#) > [Accessories](#) > [MK 023](#)

MK 023 (635.023.0)

Voltage measuring head for direct voltage measurement up to ± 4 kV for the EFM 022/023.



For measurement, the voltage measuring head MK 023 is attached to the front of the modulator system of the electric field meter instead of the spacers.

Since the internal Teflonized measuring plate is arranged at a distance of 1cm, you now choose Distance = 1cm.

The measured values are now shown directly in the display.

This resulting linear voltmeter has the following excellent properties:

Input capacitance: 5pF

Input resistance: > 10¹⁵ Ω

Search:

Come on