

PRODUCT DATA SHEET

VS 15 B

Varioshake shakers are equipped with a large number of possible shaking movements for a wide variety of applications. Reciprocating shakers are used in laboratories and incubation and temperature control rooms at ambient temperatures between 10 and 60 °C for shaking bottles, test tubes or separating funnels.



Technical Attributes	VS 15 B
Ambient temperature min.	10 °C
Ambient temperature max.	50 °C
Shaking platform width	450 mm
Shaking platform depth	450 mm
Load capacity max.	15 kg
Shaking amplitude	30 mm
Shaking frequency min.	20 min ⁻¹
Shaking frequency max.	300 min ⁻¹
Shaking motion	reciprocating
Timer	1 minute - 99:59 hours or continuous operation
Dimensions (WxDxH) in mm	480x487x160
Weight	19.5 kg

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser