

UEE SERIES-PORTABLE HARDNESS TESTER UEE910

WARRANTY
3 YESRS



FUNCTIONS & FEATURES

- High quality and precision.
- Automatically identify 7 types of Impact devices for special application.
- Freely switch to hardness scales HRB, HRC, HV, HB, HS, HL.
- Direct calibration on HL,HRC,HB.
- PC Software for data transmission, analysis and measurement reports printing.
- Test at any angle, even upside down.
- Large LCD screen with back-light, showing all functions and parameters.
- Upper and lower limit and sound alarm.
- Conversion to tensile strength (U.T.S).
- 3 years warranty and life-long services.

MEASURING MATERIALS

- 10 types of metals: steel and cast steel, alloy tool steel, stainless steel, gray cast iron, nodular cast iron, cast aluminum alloy, copper zinc alloys, copper and tin alloy, copper, forged steel.

TECHNICAL PARAMETERS

Model	Uee910
Measuring Range	(170-960)HLD,(17.9-69.5)HRC,(19-683)HB,(80-1042)HV,(30.6-102.6)HS,(13.5-101.7)HRB
Hardness parameter	HL, HRC,HRB, HS,HB,HV
Accuracy	±6HLD
Memory	600 groups
PC Connection	Available
Battery	2*AA
Operating Temperature	-20°C~+60°C
Dimensions	163×78×33mm
Weight	240g
Standard Configuration	Main unit, Impact Device type D, Calibration block,Small supporting ring, USB cable, Software, Backup accessories(Impact ball*1, Cable*1, Spanner *1), Cleaning brush,Operation manual,Certificate.
Optional Accessories	Optional Impact Devices(D,DC,DL,D+15,G,C,E), Shaped support rings, Testing blocks

Pictures



UEE SERIES-PORTABLE HARDNESS TESTER UEE912

WARRANTY
3 YESRS



FUNCTIONS & FEATURES

- High quality metal shell
- Precise measuring performance
- Automatically identify 7 types of Impact devices for special application
- Direct calibrate on HL,HRC,HB, and freely switch to 6 different hardness scales
- Test at any angle, even upside down
- Large LCD screen with back-light, showing all functions and parameters
- Conversion to tensile strength (U.T.S)
- PC Software for data transmission, analysis and measurement reports printing
- 3 years warranty and life-long services

MEASURING MATERIALS

- 10 types of metals: steel and cast steel, alloy tool steel, stainless steel, gray cast iron, nodular cast iron, cast aluminum alloy, copper zinc alloys, copper and tin alloy, copper, forged steel.

TECHNICAL PARAMETERS

Model	Uee912
Measuring Range	(170-960)HLD,(17.9-69.5)HRC,(19-683)HB,(80-1042)HV,(30.6-102.6)HS,(13.5-101.7)HRB
Hardness parameter	HL, HRC,HRB, HS,HB,HV
Accuracy	±6HLD
Memory	600 groups
PC Connection	Available
Battery	2*AA
Operating Temperature	-20°C~+60°C
Dimensions	130×70×30mm
Weight	300g
Standard Configuration	Main unit, Impact Device type D, Calibration block,Small supporting ring, USB cable, Software, Backup accessories(Impact ball*1, Cable*1, Spanner *1), Cleaning brush, Coin screwdriver, Operation manual,Certificate.
Optional Accessories	Optional Impact Devices(D,DC,DL,D+15,G,C,E), Shaped support rings, Testing blocks

Pictures



UEE SERIES-PORTABLE HARDNESS TESTER UEE915

WARRANTY
3 YESRS



FUNCTIONS & FEATURES

- High stability and precision
- With built-in thermal printer
- Rechargeable Li-ion battery and auto power-off function
- Direct calibrate on HL,HRC,HB, and freely switch to 8 different hardness scales
- Automatically identify 7 types of Impact devices for special application
- Test at any angle and direction, even upside down
- Conversion to tensile strength (U.T.S)
- PC Software for data transmission, analysis and measurement reports printing
- 3 years warranty and life-long services

MEASURING MATERIALS

- 10 types of metals: steel and cast steel, alloy tool steel, stainless steel, gray cast iron, nodular cast iron, cast aluminum alloy, copper zinc alloys, copper and tin alloy, copper, forged steel.

Pictures



Calibration on
HLD/HRC/HRB Blocks



Water-proof packing box



Receiving Measurement Data



Select Test Conditions