

Home About Us Products V Applications V Standards V Successful Cases News V E-Catalog Contact Us

Home > Products > Electrodynamic Vibration Generator System

Product Categories

Goniophotometer >

Spectroradiometer >

Integrating Sphere >

LED Test Instruments >

CFL Testing Instruments >

Photometer and Colorimeter >

EMI and EMC Test Systems >

Electronic Ballast Tester >

Electrical Safety Tester >
Environmental Test Chamber >

Plug and Switch Testing >

AC and DC Power Supply >

Object Color and Glossiness Test >

Mask Produce and Test Machine >

Electronic Components Test >

Related Applications



LED Driver Test Solutions



Mobile and Network Test Solutions



LEDs and Luminaire Test Solutions

Related Technical Articles

Basic Environmental Test for Luminaire According to IEC 60068

AMA: LED Street Light above 3000K Bears More Health Risks

IEC60598 General Requirements and Testing

Related Successful Case

Saudi Arabia-Free installation and training for the customer who purchased the JL-34 Swing Pipe Water Spray Test Equipment and IK07-10 Level Tester

Algeria – LISUN Engineer do installation and training for our clients about environmental chambers, vibration table and surge generator

Columbia – Installation for waterproof & dustproof test, goniophotometer, temperature humidity chamber, vibration table, UV lamps aging chamber, etc





Electrodynamic Vibration Generator System

Product No: LVD-100KG

Get a Quote Your email address will not be published. Required fields are marked * Name* Company* Email* Cell/WhatsApp Message*



Description Video Download

LVD-100KG/LVD-100KG-6D Electrodynamic Vibration Generator Test Table is according to IEC 60068, IEC68-2-6, JJG189-97, GB/T13309-91, GB2423 and other relevant standards.

Send

- LVD-100KG: Combined vertical table and horizontal table in one set
- LVD-100KG-6D: Combined vertical table and two directions horizontal table in one set

Measurements:

Sine Wave, Frequency Modulation, Sweep Frequency, Programmable, Frequency Doubling, Logarithm, High Acceleration speed, Amplitude Modulation, Time Control, Full-function Computer Control, simple and easy to set the acceleration and amplitude.

Specifications:

- Vibration table size: 500*500mm (Other size can be designed)
- Vibration: 0~5mm (Adjustable range P-P). Vibration waveform: sine wave (half wave and full wave). Acceleration speed: 0~20g (Adjustable)
- Maximum test load capacity: 100kg
- Accuracy: Frequency can be displayed to 0.01 Hz. Precision: 0.1 Hz.
- Sweep frequency function (1~600Hz): (Upper frequency, Lower frequency, Time range) It can set real standard arbitrarily to sweep frequency back and forth
- Programmable Function (1~600Hz): It can set 15 segments in one test with different parameters (frequency/amplitude/time/acceleration), and it can be recycled
- Frequency doubling function (1~600Hz): 15 segments multiplied-increase:

1)Low to high frequency

2)High to low frequency

3)Low to high and then to low frequency, it can be recycled

 \bullet Logarithmic function (1~600Hz), 3 modes of logarithm/can be recycled:

1)Lower to upper frequency

2)Upper to lower frequency

3)Lower to upper and then to lower frequency

- Measuring instrument: To display amplitude, acceleration speed and the maximum acceleration speed
- The Y type jig in the product picture is according to the customer's design for option, it isn't included in the quotation.

C

Related Products

←



Home About Us Products V Applications V Standards V Successful Cases News V E-Catalog Contact Us







SC-015 Dustproof Testing Machine



JL-X Waterproof Test



GDJS-015B High and Low Temperature Humidity Chamber

About Us | Contact Us | Blog | Privacy











© Copyright 2003-2020. All Rights Reserved