

## SINGLE-PHASE [SS] - BASIC - RACK 19" - AUTO TRANSFORMER



Part Number	BB-1.5-SS-R-AU	BB-03-SS-R-AU	BB-05-SS-R-AU	BB-7.5-SS-R-AU
Power	1.5 kVA	3 kVA	5 kVA	7.5 kVA
Transformer	Auto Transformer			
Full Load Efficiency	> 93%			
<b>VOLTAGE</b>				
Input Range	190 - 267 Vac			
Output Ranges and Switch Mode	LOW 2-150Vac HIGH 4-300Vac Switch LOW/HIGH through local control panel and remote interfaces			
Regulation System	Local Control Panel: 125Vac ± 25Vac and 250Vac ± 50Vac Remote Control Interfaces: 2-150Vac and 4-300Vac			
Sensing	Yes - (Maximum Voltage Drop 5%)			
Total Harmonic Distortion (THD)	< 1%			
Static Line Regulation	< 1%			
Static Load Regulation	< 1%			
Dynamic stability of the output voltage upon load variation	< 0.5%			
Time Response to load or line variation	< 1 ms			
<b>CURRENT</b>				
Max Current Setup	-			
Regulation Function	-			
RMS at 150Vac and 300Vac	10 A - 5 A	20 A - 10 A	33,3 A - 16,6 A	50 A - 25 A
Inrush at 150Vac and 300Vac [6s]	15 A - 7,5 A	30 A - 15 A	50 A - 25 A	75 A - 37,5 A
<b>FREQUENCY</b>				
Input Range	47Hz - 63Hz			
Output (switchable)	50Hz and 60 Hz [± 0,01%]			
Additional Output Value (switchable)	-			
Regulation Function (adjustable)	-			
<b>PHASES</b>				
Offset Modulation	-			

OTHERS				
Crest factor	04:01			
Noise level	Min 30dba Max 60dBA			
Power Protections	OVP, UVP, OCP, OTP			
CONTROL PANEL				
LCD Display	LCD 2 x 16 characters			
Voltage and current LCD Display accuracy	± 2 DIGIT			
Voltage and current LCD Display resolution	± 0.5			
Cos φ value visualization	-			
Frequency value visualization	-			
7" LCD Touch Panel Control	-			
COMMUNICATION INTERFACES				
Analog	I/O 12 poles equipped with 0-10Vdc [accuracy response ± 1%]			
RS232	Yes			
Ethernet	Yes			
Communication Protocols / Drivers	SCPI (over RS-232 and Ethernet) / LabView Drivers			
Reference Voltage of remote controls	Common ground with ground line			
MECHANICAL [autotransformer / isolation transformer]				
Plate Dimensions (W x H x D)	-	-	-	-
Plate Weight	-	-	-	-
Rack19" Dimensions	3U D540 including 40mm handles	3U D540 including 40mm handles	3U D540 including 40mm handles	3U D540 including 40mm handles
Rack 19" Weight	14 kg	18 kg	22 kg	29 kg
Tower Dimensions (W x H x D)	-	-	-	-
Tower Weight	-	-	-	-
ENVIRONMENTAL				
Cooling	Air Forced Circulation with automatic fan speed regulation			
Operating Temperature	from 0° to +40°C			
Storage Temperature	from -40° to +85°C			