

THREE-PHASE SINGLE-PHASE [TS] - BASIC - RACK 19" - AUTO TRANSFORMER



Part Number	BB-10-TS-R-AU	BB-17.5-TS-R-AU	-
Power	10 kVA	17.5 kVA	-
Transformer	Auto Transformer		
Full Load Efficiency	> 93%		
VOLTAGE			
Input Range	350 – 440 Vac		
Output Ranges and Switch Mode	LOW 2-150Vac HIGH 4-300Vac		
Regulation System	Local and Remote: 2-150Vac and 4-300Vac		
Sensing	Yes - (Maximum Voltage Drop 5%)		
Total Harmonic Distortion (THD)	< 1%		
Static Line Regulation	< 1%		
Static Load Regulation	< 1%		
Dynamic stability of the output voltage upon load variation	< 0.5%		
Time Response to load or line variation	< 1 ms		
CURRENT			
Max Current Setup	-		
Regulation Function	-		
RMS at 150Vac and 300Vac	66 A / 33 A	116,6 A / 58,3 A	-
Inrush at 150Vac and 300Vac [6s]	99 A / 49,5 A	175 A / 87,5 A	-
FREQUENCY			
Input Range	47Hz - 63Hz		
Output (switchable)	50Hz and 60 Hz [± 0,01%]		
Additional Output Value (switchable)	-		
Regulation Function (adjustable)	-		
PHASES			

Offset Modulation	-		
OTHERS			
Crest factor	04:01		
Noise level	60dBA		
Power Protections	OVP, UVP, OCP, OTP		
CONTROL PANEL			
LCD Display	Rack 19" - 2 LED strings		
Voltage and current LCD Display accuracy	± 2 DIGIT		
Voltage and current LCD Display resolution	± 0.5		
Cos φ value visualization	-		
Frequency value visualization	-		
7" LCD Touch Panel Control	-		
COMMUNICATION INTERFACES			
Analog	I/O 10 poles both equipped with 0-10Vdc [accuracy response ± 1%]		
RS232	Yes		
Ethernet	adapter available		
Communication Protocols / Drivers	Standard ASCII code (MCB owned) via RS232/Ethernet		
Reference Voltage of remote controls	Common ground with ground line		
MECHANICAL [autotransformer / isolation transformer]			
Plate Dimensions (W x H x D)	-	-	-
Plate Weight	-	-	-
Rack19" Dimensions	(60 ± 50) D560 Including 40mm handles	(60 ± 50) D720 Including 40mm handles	-
Rack 19" Weight	36 kg	62 kg	-
Tower Dimensions (W x H x D)	-	-	-
Tower Weight	-	-	-
ENVIRONMENTAL			
Cooling	Air Forced Circulation		
Operating Temperature	from 0° to +40°C		
Storage Temperature	from -40° to +85°C		
REGULATORY			
Safety & EMC	EN 62040-1, EN 62040-2, EN62040-3, EN 62368-1		