

## THREE-PHASE SINGLE-PHASE [TS] - MINI TOWER - BASIC - AUTO TRANSFORMER



Part Number	BB-10-TS-T-AU	BB-17.5-TS-T-AU	BB-25-TS-T-AU
Power	10 kVA	17.5 kVA	25 kVA
Transformer	Auto Transformer		
Full Load Efficiency	> 93%		
<b>VOLTAGE</b>			
Input Range	350 – 440 Vac		
Output Ranges and Switch Mode	LOW 2-150Vac / HIGH 4-300Vac		
Regulation System	Local and Remote: 2-150Vac and 4-300Vac		
Sensing	Yes - (Maximum Voltage Drop 5%)		
Total Harmonic Distortion (THD)	< 1%		
Static Line Regulation	< 1%		
Static Load Regulation	< 1%		
Dynamic stability of the output voltage upon load variation	< 0.5%		
Time Response to load or line variation	< 1 ms		
<b>CURRENT</b>			
Max Current Setup	-		
Regulation Function	-		
RMS at 150Vac and 300Vac	66 A / 33 A	116,6 A / 58,3 A	166,6 A / 83,3 A
Inrush at 150Vac and 300Vac [6s]	99 A / 49,5 A	175 A / 87,5 A	250 A / 125 A
<b>FREQUENCY</b>			
Input Range	47Hz - 63Hz		
Output (switchable)	50Hz and 60 Hz [ $\pm$ 0,01%]		
Additional Output Value (switchable)	-		

Regulation Function (adjustable)	-		
<b>PHASES</b>			
Offset Modulation	-		
<b>OTHERS</b>			
Crest factor	04:01		
Noise level	60dBA		
Power Protections	OVP, UVP, OCP, OTP		
<b>CONTROL PANEL</b>			
LCD Display	LCD 4 x 40 characters		
Voltage and current LCD Display accuracy	± 2 DIGIT		
Voltage and current LCD Display resolution	± 0.5		
Cos φ value visualization	-		
Frequency value visualization	-		
7" LCD Touch Panel Control	-		
<b>COMMUNICATION INTERFACES</b>			
Analog	I/O 12 poles equipped with 0-10Vdc [accuracy response ± 1%]		
RS232	Yes		
Ethernet	Yes		
Communication Protocols / Drivers	SCPI over RS232 and Ethernet		
Reference Voltage of remote controls	Common ground with ground line		
<b>MECHANICAL [autotransformer / isolation transformer]</b>			
Plate Dimensions (W x H x D)	-	-	-
Plate Weight	-	-	-
Rack19" Dimensions	-	-	-
Rack 19" Weight	-	-	-
Tower Dimensions (W x H x D)	550 x 1100 x 800 mm	550 x 1100 x 800 mm	550 x 1100 x 800 mm
Tower Weight	95 kg	100 kg	120 kg
<b>ENVIRONMENTAL</b>			
Cooling	Air Forced Circulation		
Operating Temperature	from 0° to +40°C		
Storage Temperature	from -40° to +85°C		
<b>REGULATORY</b>			
Safety & EMC	EN 62040-1, EN 62040-2, EN62040-3, EN 62368-1		