

SINGLE-PHASE [SS] - PREMIUM - RACK 19" - LCD 4 x 40 - ISOLATION TRANSFORMER


| | | | | |
|---|--|--------------------------------|--------------------------------------|--------------------------------------|
| Part Number | BP-1.5-SS-R-IS | BP-03-SS-R-IS | BP-05-SS-R-IS | BP-7.5-SS-R-IS |
| Power | 1.5 kVA | 3 kVA | 5 kVA | 7.5 kVA |
| Transformer | Isolation Transformer | | | |
| Full Load Efficiency | > 93% | | | |
| VOLTAGE | | | | |
| Input Range | 190 - 267 Vac [LOW 2-150Vac HIGH 4-300Vac Manual and Automatic Switch LOW/HIGH through control panel and remote interface] | | | |
| Output Ranges and Switch Mode | Local [Command Buttons] and Remote [Interfaces]; 2-150Vac and 4-300Vac | | | |
| Regulation System | Local [Command Buttons] and Remote [Interfaces]; 2-150Vac and 4-300Vac | | | |
| Sensing | Yes - (Maximum Voltage Drop 5%) | | | |
| Total Harmonic Distortion (THD) | < 1% | | | |
| Static Line Regulation | < 1% | | | |
| Static Load Regulation | < 1% | | | |
| Dynamic stability of the output voltage upon load variation | < 0.5% | | | |
| Time Response to load or line variation | < 1 ms | | | |
| CURRENT | | | | |
| Max Current Setup and Current Regulation | 3 working modes (M1, M2, M3) M1: set of I _{max} within the current range and power-off of the unit when the load exceeds the set current M2: set of I _{max} within the current range and proportional decrease of the voltage when the load exceeds the set current M3: current generator mode with voltage automatically set at the highest value within the selected voltage range (not adjustable) and the current freely adjustable within certain load impedance criterias | | | |
| RMS at 150Vac and 300Vac | 10 A - 5 A | 20 A - 10 A | 33,3 A - 16,6 A | 50 A - 25 A |
| Inrush at 150Vac and 300Vac [6s] | 15 A - 7,5 A | 30 A - 15 A | 50 A - 25 A | 75 A - 37,5 A |
| FREQUENCY | | | | |
| Input Range | 47Hz - 63 Hz | | | |
| Output (switchable) | 50Hz and 60 Hz [± 0,01%] | | | |
| Additional Output Value (switchable) | 400Hz [± 0,01%] | | | |
| Regulation Function (adjustable) | from 40Hz to 80Hz [± 0,01%] | | | |
| PHASES | | | | |
| Offset Modulation | - | | | |
| OTHERS | | | | |
| Crest factor | 04:01 | | | |
| Noise level | Min 30dba Max 60dba | | | |
| Power Protections | OVP, UVP, OCP, OTP | | | |
| CONTROL PANEL | | | | |
| LCD Display | [4 x 40 characters] | | | |
| Voltage and current LCD Display accuracy | ± 2 DIGIT | | | |
| Voltage and current LCD Display resolution | ± 0.5 | | | |
| Cos φ value visualization | Yes | | | |
| Frequency value visualization | Yes | | | |
| 7" LCD Touch Panel Control | - | | | |
| COMMUNICATION INTERFACES | | | | |
| Analog | I/O 12 poles equipped with 0-10Vdc [accuracy response ± 1%] | | | |
| RS232 | Yes | | | |
| Ethernet | Yes | | | |
| Communication Protocols / Drivers | SCPI (over RS-232 and Ethernet) / LabView Drivers | | | |
| Reference Voltage of remote controls | Common ground with ground line | | | |
| MECHANICAL [autotransformer / Isolation transformer] | | | | |
| Plate Dimensions (W x H x D) | - | - | - | - |
| Plate Weight | - | - | - | - |
| Rack19" Dimensions | 3U D540 including 40mm handles | 3U D540 including 40mm handles | 2 X [3U D540] including 40mm handles | 2 X [3U D540] including 40mm handles |
| Rack 19" Weight | 21 kg | 27 kg | 37 kg | 44 kg |
| Tower Dimensions (W x H x D) | - | - | - | - |
| Tower Weight | - | - | - | - |
| ENVIRONMENTAL | | | | |
| Cooling | Forced Circulation | | | |
| Operating Temperature | from 0° to +40°C | | | |
| Storage Temperature | from -40° to +85°C | | | |
| REGULATORY | | | | |
| Safety & EMC | EN 62040-1, EN 62040-2, EN62040-3, EN 62368-1 | | | |