



Master  
Custom  
Balance

## POWER-BOOST - PREMIUM

QMS - Quality Management System  
UNI EN ISO 9001:2015  
Certificate n. 50 100 5422



SINGLE-PHASE [SS] - PREMIUM - RACK 19" - LCD 7" TOUCH SCREEN - AUTO TRANSFORMER



Part Number	BPS-1.5-SS-R-AU	BPS-03-SS-R-AU	BPS-05-SS-R-AU	BPS-7.5-SS-R-AU
Power	1.5 kVA	3 kVA	5 kVA	7.5 kVA
Transformer	Auto Transformer			
Full Load Efficiency	> 93%			
<b>VOLTAGE</b>				
Input Range	190 - 267 Vac			
Output Ranges and Switch Mode	LOW 2-150Vac HIGH 4-300Vac Manual and Automatic Switch LOW/HIGH through control panel and remote interface			
Regulation System	Local [Command Buttons] and Remote [Interfaces]: 2-150Vac and 4-300Vac			
Sensing	Yes - (Maximum Voltage Drop 5%)			
Total Harmonic Distortion (THD)	< 1%			
Static Line Regulation	< 1%			
Static Load Regulation	< 1%			
Dynamic stability of the output voltage upon load variation	< 0.5%			
Time Response to load or line variation	< 1 ms			
<b>CURRENT</b>				
Max Current Setup and Current Regulation	3 working modes (M1, M2, M3)  M1: set of Imax within the current range and power-off of the unit when the load exceeds the set current  M2: set of Imax within the current range and proportional decrease of the voltage when the load exceeds the set current  M3: current generator mode with voltage automatically set at the highest value within the selected voltage range (not adjustable) and the current freely adjustable within certain load impedance criterias			
RMS at 150Vac and 300Vac	10 A - 5 A	20 A - 10 A	33,3 A - 16,6 A	50 A - 25 A
Inrush at 150Vac and 300Vac [6s]	15 A - 7,5 A	30 A - 15 A	50 A - 25 A	75 A - 37,5 A
<b>FREQUENCY</b>				
Input Range	47Hz - 63 Hz			
Output (switchable)	50Hz and 60 Hz [ $\pm 0,01\%$ ]			
Additional Output Value (switchable)	400Hz [ $\pm 0,01\%$ ]			
Regulation Function (adjustable)	from 40Hz to 80Hz [ $\pm 0,01\%$ ]			
<b>PHASES</b>				
Offset Modulation	-			
<b>OTHERS</b>				

Crest factor	04:01			
Noise level	Min 30dba Max 60dba			
Power Protections	OVP, UVP, OCP, OTP			
<b>CONTROL PANEL</b>				
LCD Display	LCD 7" Touchscreen			
Programmability	Yes (Ramps and ON/OFF)			
Voltage and current LCD Display accuracy	± 2 DIGIT			
Voltage and current LCD Display resolution	± 0.5			
Cos φ value visualization	Yes			
Frequency value visualization	Yes			
<b>COMMUNICATION INTERFACES</b>				
Analog	I/O 12 poles equipped with 0-10Vdc [accuracy response ± 1%]			
RS232	Yes			
Ethernet	Yes			
Communication Protocols / Drivers	SCPI (over RS-232 and Ethernet) / LabView Drivers			
Reference Voltage of remote controls	Common ground with ground line			
<b>MECHANICAL [autotransformer / isolation transformer]</b>				
Plate Dimensions (W x H x D)	-	-	-	-
Plate Weight	-	-	-	-
Rack19" Dimensions	3U D540 including 40mm handles	3U D540 including 40mm handles	3U D540 including 40mm handles	3U D540 including 40mm handles
Rack 19" Weight	14 kg	18 kg	22 kg	29 kg
Tower Dimensions (W x H x D)	-	-	-	-
Tower Weight	-	-	-	-
<b>ENVIRONMENTAL</b>				
Cooling	Forced Circulation			
Operating Temperature	from 0° to +40°C			
Storage Temperature	from -40° to +85°C			
<b>REGULATORY</b>				
Safety & EMC	EN 62040-1, EN 62040-2, EN62040-3, EN 62368-1			