

Features

- Direct mV drop reading
- 100A DC test current
- Minimum resolution of 0.1 $\mu\Omega$
- Calibration due indicator
- CE Compatible
- Built in thermal printer & PC interface through USB
- Specially designed for measurement of contact resistance of circuit breakers
- Mains and Battery operated
- Internal memory of 99 test results
- Tri colour LED for Mains/Battery/LOBAT
- Date & time display
- Rust removing 'C' clamp



PCRM-100S

Contact Resistance Meter

The Motwane make Contact Resistance Meter (Model:PCRM-100S) is a digital micro-ohmmeter, specially designed to measure extremely low resistances in micro ohm. The Instrument is based on Kelvin 4- wire connection method for measurement of low resistance.

The Current injection is fixed at 100A. Test information like current injected with measured resistance & voltage drop is displayed with real time data on large LCD with backlit.

This User friendly Instrument and it's accessories are housed in easy transportation case. Advanced Windows based software is provided for data downloading, analysis and report generation. Internal memory of 99 records is provided for onsite data storage. Thermal printer is the additional feature provided to print the test results.

Applications

PCRM-100S is specially used to measure static contact resistance of HT LT circuit breaker contacts installed in energised switchyards. High accuracy and repeatability makes it a reliable tool for Quality Assurance and easy operation makes it a very handy tool for quick maintenance checks in various industries.

Typical resistance measurement applications are:

- Circuit Breaker contact resistance
- Bus bar joints
- Isolator contacts
- Weld joints
- Bond resistance

PCRM-100S

Technical Specification

- Test Currents : 100A DC
- Range & Resolution : 200μΩ with 0.1μΩ
2000μΩ with 1μΩ
- Measurement Principle : Four wire measurement
- Basic Accuracy : ± 2% of reading ± 1 Digit.
(From 10% of the range).
- Memory Storage : 99 reading storage facility.
- Computer Interface : USB
- Thermal Printer : For printing the test results.
- Display : Custom Built 3 ½ digit LCD
Display with Backlit.

Physical Specifications

- Enclosure Material : ABS.
- Dimensions : 365mm x 465mm x 185mm.
(D X W X H)
- Gross Weight : 20Kg Approx.
(Instrument with Standard
Accessories)

Power Supply

- Mains : 230V ±10%, 50Hz ±10Hz
Single phase AC supply.
- Battery : 12V-7.5AH.
(Rechargeable)
- Power Consumption : 35VA, 6.0 Watt on battery.

Environmental

- Operating Temperature : 0°C to 55°C.
- Storage Temperature : 0°C to 50°C.
- Humidity : less than 95% RH, Non
condensing.

Safety

- Directives for CE Certification:
LVD: 2006/95/EC EMC: 2004/104/EC.
- Relevant Standard Specification (S):
EN61010-1, EN61326-1.

Accessories

Standard Accessories

- 1 set of 15 meter strong cable with C Clamp 75mm opening
- 1 set of Master Earthing Cable with battery clip (7 meter)
- Mains power cord
- User Manual
- Calibration Certificate
- Carrying Case
- Thermal Paper Role
- Spare Fuse (250mA/250V slow blow)

Optional Accessories

- 22 meter strong cable with
- C Clamp 50mm jaw size
- C Clamp 100mm jaw size
- C Clamp 150mm jaw size
- Heavy Crocodile clip 25mm jaw size
- 03 meter cable (Heavy Crocodile clip 25mm opening)
- Software CD
- USB Cord

Software Details

- Type : Windows based software
- Interface : USB
- Data Transfer : real time data
- Internal DataStorage : 99 Test results
- Features : Data down loading
Analysis and report generation



Print Report



Notes

1. The Instrument is accompanied with Test & calibration sheet. 2. Test Facilities can be provided at the factory with the available test set-ups only. 3. The company's policy is continuous improvement of its products. We therefore reserve the Right of any deviation from illustration or specifications without notice. 4. Stated accuracies are valid from 10% of the range to 95% of the range. 5. Accuracy Specified for temperature range of 25°C ± 5°C & 55% RH ± 10%

Designed and Manufactured by:

The Motwane Manufacturing Company Pvt. Ltd.

Gyan Baug, Motwane Road, Nashik 422101, Maharashtra, India.

Tel. No.: +91-253-2463752 / 53 Fax.: +91-253-2463197 Toll Free: 1800 - 233 - 7766

e-mail: sales@motwane.com visit : www.motwane.com

