



## Introduction

# OC-903 Portable Carbon Dioxide CO<sub>2</sub> gas detector



## Description:

OC-903 portable Carbon Dioxide CO<sub>2</sub> gas detector with the famous brand Infrared sensor for CO<sub>2</sub> gas inspection, with the inner pump 内部泵 and the data logger function, optional sensor for the temperature and humidity measurement.

## Features:

Semiconductor technology of ultra low power 32 bit microprocessor, 24 bit ADC acquisition chip, so with the high accuracy.

2.4 inch IPS industrial grade color screen.

Support English language menu.

The gas concentration unit support for the ppm, mg/m<sup>3</sup>, %vol.

For 1~4 gas detection, supporting single gas, two gas, three gas and four gas inspection.

With the inner pump and the suction strength is adjustable in different level.

Explosion proof grade of Ex ia IIC T4 Ga.



## Function:

Inspect the gas concentration and alarm when it up to the preset alarm level.

With auto-test and data recover function.

One-key operation to restore to factory default setting.

Temperature and pressure compensation function.

Adjustable two stage audible-visual alarm threshold value.

Powered by rechargeable lithium battery with big capacity.

Working under the micro negative pressure is available.

Overload protection, over charge protection, anti static interference, anti magnetic interference, etc.



## Technical specifications:

|                       |  |
|-----------------------|--|
| Gas type              | Carbon Dioxide(CO2)  |
| Working principle     | Infrared sensor  |
| Measuring range       | 0~5000ppm, 0~30000ppm, 0~50000ppm, 0~20% vol,<br>0~50% vol, 0~100% vol,or customized                                   |
| Resolution            | 1ppm or 0.01% vol  |
| Precision             | $\leq \pm 2\%$ F.S   |
| Sampling method       | Pump-suction sampling, flow rate of<br>100~1000mL/min.(Adjustable)   |
| Data logger function  | About 100,000 group of data capacity.  |
| Response time         | $\leq 20$ s/10s  |
| Recovery time         | $\leq 20$ s  |
| Repeatability         | $\leq \pm 1\%$   |
| Linearity             | $\leq \pm 1\%$   |
| Zero drift            | $\leq \pm 1\%$ (F.S/year)  |
| Display               | Gas type, concentration unit, value, Time, Temperature,<br>Humidity, pump and battery status                           |
| Concentration unit    | % vol, mg/m <sup>3</sup> , ppm   |
| Working environment   | Working temperature: -30~60 degree;<br>Working humidity: 0~95%RH (non-condensing);<br>Working pressure: -30Kpa~100Kpa. |
| Explosion-proof Grade | Ex ia IIC T4 Ga  |
| Protection grade      | IP65   |
| Alarm mode            | Audible-visual-vibration alarm   |
| Dimension             | 180m'm   |
| Weight                | 500g   |
| Accessory             | Box, Instruction, USB charger, Data line, Calibration cap,<br>CD   |

**Applications:**

The portable Carbon Dioxide CO<sub>2</sub> gas detector used in the gas safety inspection and alarm for industrial scene, such as petroleum refinery, chemical plants, LPG stations, boiler rooms, gas stations, paint spray booths, metallurgy, mining, fire, environmental protection, etc., where need to inspect the CO<sub>2</sub> gas concentration.