



Introduction



Description:

Semiconductor technology of ultra low power 32 bit microprocessor, 24 bit ADC acquisition chip, so with the high accuracy.

2.4 inch IPS industrial grade color screen.

Support English language menu.

The gas concentration unit support for the ppm, mg/m³, %LEL.

With the inner pump and the suction strength is adjustable in different level.

Explosion proof grade of Exia II CT4.

Features:

Semiconductor technology of ultra low power 32 bit microprocessor, 24 bit ADC acquisition chip, so with the high accuracy.

2.4 inch IPS industrial grade color screen.

Support English language menu.

The gas concentration unit support for the ppm, mg/m³, %LEL.

With the inner pump and the suction strength is adjustable in different level.

Explosion proof grade of Exia II CT4.

Function:

Inspect the gas concentration and alarm when it up to the preset alarm level.

With auto-test and data recover function.

One-key operation to restore to factory default setting.

Temperature and pressure compensation function.

Adjustable two stage audible-visual alarm threshold value.

Powered by rechargeable lithium battery with big capacity.

Working under the micro negative pressure is available.

Overload protection, over charge protection, anti static interference, anti magnetic interference, etc.

Technical specifications:

Gas type	NH3, H2S, Ex
Working principle	Catalytic combustion sensor for Ex; Electrochemical sensor for NH3 and H2S
Measuring range	Ex: 0~100%LEL, NH3: 0~100ppm, H2S: 0~100ppm
Resolution	Ex: 0.01%LEL, NH3: 0.01ppm, H2S: 0.01ppm
Precision	$\leq \pm 3\%$ F.S
Sampling method	Pump-suction sampling, flow rate of 100~1000mL/min.(Adjustable)
Data logger function	About 100,000 group of data capacity.
Response time	≤ 20 s/10s
Recovery time	≤ 20 s
Repeatability	$\leq \pm 1\%$
Linearity	$\leq \pm 1\%$
Zero drift	$\leq \pm 1\%$ (F.S/year)
Display	Gas type, concentration unit, value, Time, Temperature, Humidity, pump and battery status
Concentration unit	%lel, ppm, mg/m ³
Working environment	Working temperature: -30~60 degree; Working humidity: 0~95%RH (non-condensing); Working pressure: -30Kpa~100Kpa.
Explosion-proof Grade	Ex ia IIC T4

Protection grade	IP65
Alarm mode	Audible-visual-vibration alarm
Dimension	180m'm
Weight	500g
Accessory	Box, Instruction, USB charger, Data line, Calibration cap, CD

Applications:

The portable multi gas detector used in the gas safety inspection and alarm for industrial scene, such as petroleum refinery, chemical plants, LPG stations, boiler rooms, gas stations, paint spray booths, metallurgy, mining, fire, environmental protection, etc., where need to inspect the gas concentration of the Combustible gas and Toxic gas.