
Microplate Shaker:



Description


Microplate shaker can accommodate all SBS format plates, PCR, tissue culture & HTS. Great for mixing applications requiring specific speeds or times.

Features

- Variable shaking speed: 150~1000rpm;
- Quick and easy fitting or any standard-depth multiwall plates;
- Continuous or timed operation, with automatic switch off;
- Display will show last used settings, even after power has been turned off;
- Continue to run by last set speed and the remaining time when the power recovered;
- Operating temperature 5°C~40°C allows for use in cold rooms or incubators;
- Holds two or four microplates;
- Easy-to-use electronic timer ensures accurate count-down and repeatability of time sensitive incubations

Model	OS-07U
Speed Range	150~1000rpm
Speed Accuracy	±2rpm(300rpm) ±5rpm(150rpm~1000rpm)
Orbit Diameter	Φ2.5mm
Max.Load	2 kg
Timer	0~99h59min
Platform Dimensions	275x235x12mm
Display	LED
Ambient	5°C~40°C
Outside Dimensions(WxDxH)	296x440x151mm
PowerSupply	220V, 50Hz
Weight	15 kg

Included Accessory



Part Number	Specifications	Note
OSA13	N/A	For OS-07U

Optional Accessories



Part Number	Specifications	Note
NSA01	WxD: 180x7mm	For OS-07U



Part Number	Specifications	Note
OSA14	WxDxH: 292x275x12m	For OS-07U



Part Number	Specifications	Note
OSA15	WxDxH: 292x275x25m	For OS-07U